

LINEAR POWER LED 1500 25 W 3000 K

LEDVANCE LINEAR LED | LED batten luminaires



Areas of application

- General indoor illumination
- Corridors
- Entrance lighting
- Accent lighting
- Public areas
- Cove lighting
- Shelves, furniture integration or under cabinet mounting
- Seamless linear lighting

Product benefits

- Compact dimensions
- Easy to install in two different mounting angles
- Energy savings of up to 45 % compared to conventional linear luminaires
- Rows of up to 10 luminaires possible
- For seamless lines of light without dark spots

Product features

- High luminous efficacy: up to 100 lm/W
- Luminous flux: up to 1,450 lm
- Available with color temperature: 3,000 K, 4,000 K
- Beam angle: 140°
- Type of protection: IP20
- Lifetime: up to 30,000 h
- On/off switch on luminaire
- Different lengths available
- Certificates: CE, CB, TUEV SÜD



Product datasheet

Technical data

Electrical data

Operating mode	Electronic control gear (EVG)
Nominal wattage	25.00 W
Nominal voltage	220...240 V
Mains frequency	50/60 Hz
Nominal current	0.109 A


Photometrical data

Color temperature	3000 K
Luminous flux	2500 lm
Light color (designation)	Warm White
Color rendering index Ra	>80

Light technical data

Beam angle	140 °
------------	-------

Dimensions & weight



Length	1473 mm
Width	28.0 mm
Height	36.0 mm
Product weight	600.00 g

Colors & materials

Body material	Aluminum
Product color	White

Temperatures & operating conditions

Product datasheet

Ambient temperature range	-20...40 °C
---------------------------	-------------

Lifespan

Lifespan	30000 h
----------	---------

Capabilities

Dimmable	No
Type of connection	Plug, EU

Certificates & standards

Protection class	II
Type of protection	IP20
Protection class IK (shock resistance)	IK02

Equipment / Accessories

- Complete mounting and connecting accessories included

Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4058075000445	LINEAR POWER LED 1500 25 W 3000 K	Shipping carton box 25	1718 mm x 233 mm x 180 mm	72.05 dm ³	19491.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.