

---

## PANEL LED 600 40 W 3000 K

LEDVANCE PANEL LED 600 | LED panel luminaires



---

### Areas of application

- Direct replacement for luminaires with 4 x 18 W or 4 x 14 W fluorescent lamps
- Corridors
- Offices
- Conference rooms
- Reception areas
- Foyers
- Elevators
- Suitable for recessed ceiling systems with grid size of 600 x 600 mm

---

### Product benefits

- Energy savings of up to 50 % compared to conventional luminaires
- Easy and quick installation
- Very homogenous light
- 5 years guarantee
- External driver for extended flexibility (compatible with selected DALI drivers)
- Very slim aluminum housing (only 10.5 mm) and matt white frame

---

### Product features

- Luminaire efficacy: up to 110 lm/W
- Luminous flux: up to 4,000 lm
- Available with color temperature: 3,000 K, 4,000 K, 6,500 K
- Type of protection: IP20
- Aluminum housing, polystyrene diffuser
- Ambient temperature in operation: -10...+45 °C
- Lifetime (L70/B50): up to 50,000 h
- Certificates: CE, CB, TUEV SUED



## Product datasheet

- Available with beam angle: 120°, 90° for UGR < 19 according to EN 12464-1

# Product datasheet

## Technical data

### Electrical data

Operating mode	ECG
Nominal wattage	40.00 W
Nominal voltage	220...240 V
Mains frequency	50/60 Hz
Nominal current	0.174 A


### Photometrical data

Color temperature	3000 K
Luminous flux	4000 lm
Light color (designation)	Warm White
Color rendering index Ra	>80

### Light technical data

Beam angle	120 °
------------	-------

### Dimensions & weight



Length	595.0 mm
Width	595.0 mm
Height	10.5 mm

### Colors & materials

Body material	Aluminum
Product color	White
Cover material	Polystyrol (PS)

### Temperatures & operating conditions

## Product datasheet

Ambient temperature range	-10...45 °C
---------------------------	-------------

### Lifespan

Lifespan	50000 h
----------	---------

### Capabilities

Dimmable	No
Type of connection	Terminal, 2-pin

### Certificates & standards

Protection class	II
Type of protection	IP20

### Equipment / Accessories

– Accessories for suspension available

### Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4058075000544	PANEL LED 600 40 W 3000 K	Shipping carton box 4	695 mm x 170 mm x 645 mm	76.21 dm <sup>3</sup>	16340.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

### Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.