

SURFACE-C LED 18 W 3000 K

LEDVANCE SURFACE CIRCULAR LED | Surface-mounted LED luminaires



Areas of application

- Direct replacement for luminaires with 2 x 18 W or 2 x 26 W CFL
- Corridors
- Stairways
- Bathrooms
- Foyers

Product benefits

- Energy savings of up to 55 % compared to conventional luminaires
- Easy and quick installation
- Very homogenous light
- LED protected for safe installation
- 3 years guarantee

Product features

- Luminaire efficacy: up to 80 lm/W
- Luminous flux: up to 1,920 lm
- Available with color temperature: 3,000 K, 4,000 K
- Beam angle: 120°
- Type of protection: IP44
- Impact resistance: IK03
- Aluminum housing, PMMA cover
- Ambient temperature in operation: -20...+40 °C
- Lifetime (L70/B50): up to 30,000 h



Product datasheet

- Certificates: CE, CB, TUEV SUED
- Versions with movement and daylight sensor available (microwave sensor)

Product datasheet

Technical data

Electrical data

Operating mode	Electronic control gear (EVG)
Nominal wattage	18.00 W
Nominal voltage	220240 V
Mains frequency	50/60 Hz
Nominal current	0.078 A


Photometrical data

Color temperature	3000 K
Luminous flux	1440 lm
Light color (designation)	Warm White
Color rendering index Ra	>80

Light technical data

Beam angle	120 °

Dimensions & weight



Diameter	350.0 mm
Height	115.0 mm

Colors & materials

Body material	Metal
Product color	White

Temperatures & operating conditions

Ambient temperature range -2040 °C

Product datasheet

Lifespan

Capabilities

Dimmable	No
Type of connection	Terminal, 3-pin

Certificates & standards

Protection class	I
Type of protection	IP44

Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4058075000742	SURFACE-C LED 18 W 3000 K	Shipping carton box 5	625 mm x 410 mm x 410 mm	105.06 dm ³	5200.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.