


MIMIK 20 CP/T2




Part number	303754
Lampholder:	LED
Light Source:	LED
Wattage:	26 W
Finish:	GR-94 / Metallic grey / Textured
Insulation class:	I
Degree of protection:	IP65
IK-J-xxIP:	IK06 1J xx3
CRI:	70
Kelvin:	3000
Power factor / COS Φ:	>0.9
Optic:	Pedestrian and cycle reflector type 2
Lightsource lumen output:	3120 lm
Luminaire lumen output:	2346 lm
L:	L80
B:	B10
Lifetime:	60000 h
Ta MIN luminaire (°C):	-20
Ta MAX luminaire (°C):	35
ULR:	0%




Description

- Wall, ceiling and post mounted luminaire for indoor and outdoor lighting, comprising:
 - Die-cast aluminium housing, powder-polyester coated ISO 9227
 - Transparent, tempered, flat glass diffuser, screen-printed inside for the MIMIK versions
 - Anti-ageing silicone gasket
 - Built-in driver
 - MIMIK luminaires are equipped with high-transmittance polycarbonate lenses with different light distributions to meet the most diverse lighting requirements
 - "CP" versions feature asymmetric light distribution suitable for bicycle and pedestrian pathways
 - Photometric data measure according to UNI EN 13032-4 and IES LM-79-08

Photometric data




Technical drawings



OPTIONAL ACCESSORIES

MIMIK CP/T2 - CP/T3 - A60/W



310444

Customising ring / Facade Accessory

Metallic grey
