

LEVANTO PLN LED1X3650 G091 T830 OP • 1103387


Product:	Levanto PLN LED1x3650 G091 T830 OP
Order code:	1103387
Family:	Levanto PLN LED
Product group:	Recessed luminaires

GENERAL DATA

Description:	Recessed mounted LED panel Light distribution type: direct Optical system: opal diffuser, UGR≤22 Housing: aluminum Colour: white (RAL9016)
Installation:	In modular suspended ceilings (600), in ceilings with cut-out openings (accessories to be ordered separately). Cable, 0.1m, 2x0.75mm ²
Environment	Indoor
Application	office, education, corridor, retail, public place

ELECTRICAL DATA

Mains voltage:	220-240V, 50/60Hz	System power*, W:	36
Power factor:	>0,9	Control gear:	ECG on/off
Integrated sensor:	None	Connection:	Cable, 0.1m, 2x0.75mm ²

LIGHTING DATA

Light source and cap, W:	LED	Light source included:	yes
Luminaire output*, lm (ta+25°C):	3600	System efficacy, lm/W:	100
CRI (Ra):	80+	CCT, K:	3000
SDCM:	5	Light Distribution:	Symmetrical wide beam (76°...125°)
Distribution Type:	Direct	Beam angle, °:	111
UGR index:	≤22	LED lifetime, h:	50000/L70B50

TECHNICAL DATA


Net weight, kg:	1.8	Quantity in package, pcs:	1
Packaging volume, m³/pcs:	0.0134	Pallet quantity, pcs:	75
Dimensions, mm:	1195x295x33		

STANDARDS


Operating temperature range, °C:	ta 0...+35	Protection class IEC:	II
Ingress protection code:	IP40	Mechanical impact resistance:	IK02
EEC:	A+	Certificates:	CE, RoHS
Warranty:	3 years		

Technical drawing (.jpg)

Light distribution curve (.jpg)



L, mm	W, mm	weight, kg
595	595	1.80
1195	295	1.80

**Note:**

Tolerance range for optical and electrical data: $\pm 10\%$. Values apply to an ambient temperature of 25°C. NORTHCLIFFE LIGHTING is constantly developing and improving its products. The right is reserved to change any product specifications without prior notification

Date of issue: 2021-10-29 ■ NORTHCLIFFE LIGHTING, UAB ■ Raudondvario pl. 101, LT-47184 Kaunas, Lithuania ■ info@northcliffe.org ■ www.northcliffe.org