



BARAT LED1X6850 D563 T840 PC/PC OP LT80 1G • 1025739**TECHNICAL DATA**

Mains voltage:	220-240V, 0/50/60Hz
Power factor:	>0,97
Connection:	Push-in terminal, 5x2x2.5mm ²

System power*, W:	50.2
Control gear:	ECG on/off

LIGHTING DATA

Light source and cap, W:	LED	Light source included:	yes
System efficacy, lm/W:	136	CRI (Ra):	80+
CCT, K:	4000	Distribution Type:	Direct
Beam angle, °:	123x102°	LED lifetime, h:	75000/L80B50

TECHNICAL DATA

Net weight, kg:	2.1	Quantity in package, pcs:	1
Packaging volume, m3/pcs:	0.016571192	Pallet quantity, pcs:	60
Dimensions, mm:	1272x96x111		

STANDARDS


Operating temperature range, °C:	ta -20...+35	Protection class IEC:	I
Ingress protection code:	IP66	Mechanical impact resistance:	IK10
Protection symbol:	D	Glow wire test, °C:	850
EEC:	A++	Certificates:	CE, RoHS
Warranty:	3 years		

Technical drawing (.jpg)

Product:	Barat LED1x6850 D563 T840 PC/PC OP LT80 1G
Order code:	1025739
Family:	Barat LED
Product group:	Hermetiniai šviestuvai

GENERAL DATA

Description:	A waterproof IP66 LED luminaire with opal diffuser and high impact resistance Diffuser: opal polycarbonate (PC), UV stabilized, high impact resistance Body: light grey polycarbonate, UV stabilized, high impact resistance Gear tray: sheet steel, white finish Diffuser retaining clips and sealing washers from the end of the body for easy maintenance
Environment	Indoor/outdoor with roof
Application	public place, industry, warehouse, hall, parking area, sports, transport terminal



L, mm	W, mm	H, mm	D, mm	h, mm
662	96	111	350	100
	146			
1272	96		700	
	146			
1572	96		940	
	146			

Light distribution curve (.jpg)

