

ONE20M3Y



Products Low Voltage Products and Systems Enclosed Switches Enclosed Switch-Disconnectors

General Information

Extended Product Type:	ONE20M3Y
Product ID:	1SCA135536R1001
EAN:	6417019641263
Catalog Description:	ONE20M3Y Enclosed Switch Disconnecter
Long Description:	Enclosed switch 3-p. 400V AC23A 7.5kW 415V AC22A 20A Plastic enclosure IP67 Red Selector handle.

Additional Information

Cable Cross-Section:	4 mm ²
Cable Entry Position:	Up/Down
Cable Outlets Per Side:	2xM20 / 2xM20
Conventional Thermal Current (I_{the}):	Fully Enclosed 20 A
Country of Origin:	Finland (FI)
Customs Tariff Number:	85371099
Data Sheet, Technical Information:	1SCC340002B0201
Declaration of Conformity - CE:	1SCC343001D2702
Degree of Protection:	acc. to IEC 60529 IP67
EAN:	6417019641263
ETIM 5:	EC000216 - Switch disconnecter
ETIM 6:	EC000216 - Switch disconnecter
Enclosure Material:	Plastic
Handle Type:	Round handle
Instructions and Manuals:	1SCC390136M0204
Invoice Description:	ONE20M3Y Enclosed Switch Disconnecter
Minimum Order Quantity:	1 piece
Number of Poles:	3
Object Classification Code:	Q
Package Level 1 EAN:	6417019641263
Package Level 1 Gross Weight:	0.16 kg
Package Level 1 Height:	103 mm
Package Level 1 Length:	66 mm
Package Level 1 Units:	1 piece
Package Level 1 Width:	85 mm
Power Loss:	at Rated Operating Conditions per Pole 0 W
Product Main Type:	ONE20
Product Name:	Enclosed Switch Disconnecter
Product Net Depth:	84 mm
Product Net Height:	92 mm
Product Net Weight:	0.12 kg
Product Net Width:	65 mm
Rated Insulation Voltage (U_i):	acc. to IEC/EN 60664-1 690 V
Rated Operational Current AC-22A (I_e):	(380 ... 415 V) 20 A
Rated Operational Current AC-23A (I_e):	(380 ... 415 V) 15.2 A
Rated Operational Power AC-23A (P_e):	(380 ... 415 V) 7.5 kW
RoHS Information:	1SCC343002D0201
RoHS Status:	Following EU Directive 2011/65/EC
Selling Unit of Measure:	piece
Short Description:	Enclosed switch 3-p. 400V AC23A 7.5kW AC22A 20A
Handle Color:	Red

