NECTRA 7W LED 3000K WHITE



OFFICE LIGHTING





CHARACTERISTIC

059551 Index: 230V Supply voltage: Frequency: 50Hz Ingress protection IP: IP40 Impact resistance IK : **IK08** Rated power: 7W Energy efficiency class: Δ+ Electrical protection class: Ш 3000K Colour temperature : 540lm Luminous flux *:

SPECIFICATION


Downlight type fitting with an integrated energy-saving LED source. Made of lightweight aluminium and plastic. Available in two ringcolours and three power versions. Its distinctive features are low profile, light weight and very easy and fast installation. Design for both solid and modular ceilings.

APPLICATION

Designed for indoor use in common areas, passageways or to provide additional illumination in the office rooms. Due to equal surface illumination and high energy savings, it is especially recommended for public buildings. Available in three power versions and two colour options.

LUMINOUS INTENSITY DISTRIB. CURVE

NECTRA 7W LED 3000K





^{*} Initial, tolerance +/- 10%

NECTRA 7W LED 3000K WHITE



OFFICE LIGHTING

TECHNICAL DATA

Index:	059551
Supply voltage:	230V
Frequency:	50Hz
Ingress protection IP:	IP40
Impact resistance IK:	IK08
Rated power:	7W
Luminous efficacy:	77lm/W
Energy efficiency class:	A+
Electrical protection class:	II
Dimensions:	ø116/51mm
Mounting dimensions:	ø88mm
Net weight of 1 unit:	0,15
Material of the body:	Aluminium
Colour temperature:	3000K
Mounting version:	Recessed
Colour of the body:	White
Working temperature:	from -15°C to +35°C
Luminous flux*:	540lm
(EAN) European Article Number:	5905963059551
Material of the diffuser:	PC
Type of the diffuser:	Opal
Replaceable light source:	No
Nominal lamp lifespan:	30000h L70B50
Colour rendering:	Ra>80
Light source:	LED
Units per package:	1

^{*} Initial, tolerance +/- 10%



NECTRA 7W LED 3000K WHITE



OFFICE LIGHTING



TECHNICAL DRAWINGS



TECHNICAL INFORMATION





The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer.

Revision date: 2017-08-30









