



# Tempo 1 RVP151

## RVP151 MHN-TD70W IC A

### MHN-TD - 70 W - Asymmetrical

Tempo is a complete floodlighting range offering a wide choice of lamp types and symmetrical and asymmetrical reflectors. It is designed for general-purpose floodlighting, and is particularly suited to small- to medium-scale area or surface lighting. The Tempo series' compact housing guarantees optimum visual integration. Anodized-aluminum reflectors ensure a highly efficient beam distribution, while the nylon bolt caps feature a goniometric aiming device for easy adjustment and alignment. A universal mounting bracket allows ceiling, wall or surface mounting with a wide range of adjustment for both down- and uplighting. Tempo's all-weather construction is designed to make cleaning and servicing easy and fast. Access to the lamp and gear is simple, via the hinged front glass with its quick-release stainless-steel clips. All Tempo luminaires are RoHS-compliant.

### Product data

General Information		Warranty period	
Number of light sources	1 pc	Warranty period	1 years
Lamp family code	MHN-TD	Optic type outdoor	Asymmetrical
Lamp power	70 W	Constant light output	No
Light source color	842 neutral white	RoHS mark	RoHS mark
Compensation circuit	Inductive parallel compensated	Operating and Electrical	
Gear	CONV [ Conventional]	Input Voltage	230 V
Optical cover/lens type	Flat glass	Input Frequency	50 Hz
Connection	Screw connection block 3-pole	Controls and Dimming	
Cable	-	Dimmable	No
Protection class IEC	Safety class I		
CE mark	CE mark		
ENEC mark	-		

# Tempo 1 RVP151

## Mechanical and Housing

Housing Material	Aluminum die-cast
Reflector material	Aluminum
Optic material	Aluminum
Optical cover/lens material	Glass
Fixation material	Steel
Optical cover/lens shape	Flat
Optical cover/lens finish	Clear
Overall length	303 mm
Overall width	306 mm
Overall height	109 mm
Effective projected area	0.08 m <sup>2</sup>

## Approval and Application

Ingress protection code	IP65 [ Dust penetration-protected, jet-proof]
Mech. impact protection code	IK07 [ 2 J reinforced]

## Initial Performance (IEC Compliant)

Init. Corr. Color Temperature	4200 K
-------------------------------	--------


Init. Color Rendering Index	80
-----------------------------	----

## Application Conditions


Ambient temperature range	-25 to +35 °C
---------------------------	---------------

## Product Data

Full product code	871794389752000
Order product name	RVP151 MHN-TD70W IC A
EAN/UPC - Product	8717943897520
Order code	910503695018
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	1
Material Nr. (12NC)	910503695018
Net Weight (Piece)	4.100 kg



## Dimensional drawing



Tempo 1 RVP151

