

# DECOR

T5&LED  
Surface/Suspended  
Luminaire for in-line  
connection



Decor 128 M82 OP



Decor 128 M82 PRZ

<b>Type:</b>	Surface or suspended mounted luminaire for in-line connection.
<b>Specification:</b>	Three different types of louvre are optional: PAR- double parabolic reflector made of mirror aluminum with four spring locks PRZ- prismatic diffuser made of UV stable polycarbonate OP- opal diffuser made of UV stable extruded polycarbonate Deluxe version louvres are manufactured using Alanod MIRO® aluminum with 95% reflectiveness. Body made of extruded aluminum profile powder painted in textured RAL 9006. Aluminum end caps fixed by two screws. Luminaire with an option "L" is used for in-line connection. Luminaire is plastic-wrapped and boxed individually.
<b>Installation:</b>	Surface luminaire designed to be fixed to ceilings of any type or suspended. Wire suspension set available on request (see option list).
<b>Application:</b>	Office buildings, shops and other commercial environments.



Wire suspension set (**SUS2**) and plastic cap with spiral cable (**CAPW**) are available on request. For more information see in Option list.

Type	Lamp (W) and socket	Overall dimensions, mm	Weight, kg	Total wattage, W
Decor 114 M80	1x14 (G5)	60x576x70	1,2	15
Decor 124 M81	1x24 (G5)	60x576x70	1,2	25
Decor 128 M82	1x28 (G5)	60x1176x70	1,9	30
Decor 135 M83	1x35 (G5)	60x1476x70	2,3	38
Decor 149 M84	1x49 (G5)	60x1476x70	2,3	53
Decor 154 M85	1x54 (G5)	60x1176x70	1,9	58
Decor 180 M86	1x80 (G5)	60x1476x70	2,4	85
Decor 2x114 N02	2x1x14 (G5)	60x1151x70	2,4	30
Decor 2x124 N03	2x1x24 (G5)	60x1151x70	2,4	50
Decor 2x128 N04	2x1x28 (G5)	60x2351x70	3,8	60
Decor 2x135 N05	2x1x35 (G5)	60x2951x70	4,6	76
Decor 2x149 N06	2x1x49 (G5)	60x2951x70	4,6	106
Decor 2x154 N07	2x1x54 (G5)	60x2351x70	3,8	116
Decor 2x180 N08	2x1x80 (G5)	60x2951x70	4,8	170

3 in one (4426 mm) and 4 in one (5901 mm) versions are available on request

Type	Overall dimensions, mm	Luminous flux, lm	Color temperature, K	Color rendering, Ra	Total wattage, W	Weight, kg
Decor LED1x1050 B161 T840 OP	60x576x70	1050	4000	>80	11	1,4
Decor LED1x1400 B429 T840 OP	60x576x70	1400	4000	>80	14	1,4
Decor LED1x2000 B430 T840 OP	60x576x70	2000	4000	>80	20	1,4
Decor LED1x2350 B163 T840 OP	60x1176x70	2350	4000	>80	23	2,2
Decor LED1x3150 B431 T840 OP	60x1176x70	3150	4000	>80	31	2,2
Decor LED1x4300 B432 T840 OP	60x1176x70	4300	4000	>80	42	2,2
Decor LED1x2950 B164 T840 OP	60x1476x70	2950	4000	>80	29	2,6
Decor LED1x4000 B433 T840 OP	60x1476x70	4000	4000	>80	40	2,6
Decor LED1x5400 B434 T840 OP	60x1476x70	5400	4000	>80	53	2,6
Decor LED1x4850 B165 T840 OP	60x2351x70	4850	4000	>80	48	4,4
Decor LED1x6550 B435 T840 OP	60x2351x70	6550	4000	>80	64	4,4
Decor LED1x8800 B436 T840 OP	60x2351x70	8800	4000	>80	86	4,4
Decor LED1x6100 B167 T840 OP	60x2951x70	6100	4000	>80	60	5,2
Decor LED1x8200 B437 T840 OP	60x2951x70	8200	4000	>80	80	5,2
Decor LED1x11100 B438 T840 OP	60x2951x70	11100	4000	>80	109	5,2

#### Options available on request:

DIM	– Dimmable ballast 1-10V	OP	– Opal cover
SWITCHDIM	– Switch DIM ballast	PRZ	– Prismatic cover
DALI	– DALI ballast	L	– Designed for in-line connection without gap (for OP/PRZ versions)
PULLSWITCH	– Pull switch device	1LIN	– Through wiring 3x1.5 mm <sup>2</sup> with two push-in terminal blocks
EMG	– Emergency version 1 hour	3LIN	– Through wiring 5x1.5 mm <sup>2</sup> with two push-in terminal blocks
EM2	– Emergency version 2 hours	RAL	– Painted RAL colour
EM3	– Emergency version 3 hours	T830	– Color temperature 3000K
5TB	– 5 way terminal block with two holes (for in and out going cable)	T840	– Color temperature 4000K
MAT	– Matted reflector (subject to minimum order)	T857	– Color temperature 5700K
PAR	– Double parabolic reflector		
MRO	– MIRO® reflector Deluxe (subject to minimum order)		



**DECOR SENSE&SOLO** series with 30 cm closed profile and designed to fulfil the needs for easy-to-use, energy saving lighting control. The basic functions are pre-programmed and are fully adjustable to meet all requirements. More information see on page 10.



ON: Auto  
OFF: Auto



15 min. → 20%  
60 sec. → Off



Bright  
out

Type	Lamp (W) and socket	Overall dimensions, mm	Weight, kg	Total wattage, W
Decor 114 P36 SENSE&SOLO	1x14 (G5)	60x876x70	1,5	15
Decor 124 P37 SENSE&SOLO	1x24 (G5)	60x876x70	1,5	25
Decor 128 P38 SENSE&SOLO	1x28 (G5)	60x1476x70	2,2	30
Decor 135 P39 SENSE&SOLO	1x35 (G5)	60x1776x70	2,6	38
Decor 149 P40 SENSE&SOLO	1x49 (G5)	60x1776x70	2,6	53
Decor 154 P41 SENSE&SOLO	1x54 (G5)	60x1476x70	2,2	58
Decor 180 P42 SENSE&SOLO	1x80 (G5)	60x1776x70	2,7	85



Decor fittings have been designed for connection in modern lighting systems with wide choice of join accessories. Thanks to interesting design and wide choice of optics, they comply with the highest lighting standards and act as an interesting element of interior design.




I-JOIN- "I" join element



T-JOIN- "T" join element



L-JOIN- "L" join element



X-JOIN- "X" join element



Fittings with 250mm closed profile from both ends are designed for connection into the lighting systems. Please add join elements ("I", "L", "T" or "X" type to the order).

Type	Lamp (W) and socket	Overall dimensions, mm	Weight, kg	Total wattage, W
Decor 114 P43	1x14 (G5)	60x1070x70	1,2	15
Decor 124 P44	1x24 (G5)	60x1070x70	1,2	25
Decor 128 P45	1x28 (G5)	60x1670x70	1,9	30
Decor 135 P46	1x35 (G5)	60x1970x70	2,3	38
Decor 149 P47	1x49 (G5)	60x1970x70	2,3	53
Decor 154 P48	1x54 (G5)	60x1670x70	1,9	58
Decor 180 P49	1x80 (G5)	60x1970x70	2,4	85
Decor 2x114 P50	2x1x14 (G5)	60x1640x70	2,4	30
Decor 2x124 P51	2x1x24 (G5)	60x1640x70	2,4	50
Decor 2x128 P52	2x1x28 (G5)	60x2840x70	3,8	60
Decor 2x135 P53	2x1x35 (G5)	60x3440x70	4,6	76
Decor 2x149 P54	2x1x49 (G5)	60x3440x70	4,6	106
Decor 2x154 P55	2x1x54 (G5)	60x2840x70	3,8	116
Decor 2x180 P56	2x1x80 (G5)	60x3440x70	4,8	170
DECOR I-JOIN		60x60x70	0,3	
DECOR L-JOIN		60x60x70	0,3	
DECOR T-JOIN		60x60x70	0,3	
DECOR X-JOIN		60x60x70	0,3	



Brackets set (**DECOR WALL BR2**) for DECOR series mounting directly to the wall with up or down lighting.



**DECOR 128 M82 PAR**

