


Sensor/actuator combinations
Blind actuator sensor, 1/1gang
for ABB-free@home®



For controlling blind or awning motors.

With integrated blind actuator.

Blind function is available also without prior programming (pre-configured).

Configuration can be changed later via the web interface (groups, scenes, etc.).

For contacting 1gang rocker 6230-10-xxx, 6231-10-xxx, 6232-10-xxx, 6233-10-xxx und 6234-10-xxx.

The bus can be connected via enclosed terminal block.

When installing in the flush-mounted box, a spatial division between the bus cable and 127 V/230 V installation cable is to be adhered to! If this minimum distance is not possible, use electronic boxes or insulating tubes.

Control element: Switch contacts top/bottom, Display elements: LED as light for orientation or display of the switching state,

Bus voltage: 24 V,

Outputs: 2 Change-over contacts/normally open contact, potential-bound, Suitable for: Operation mode Blind,

Rated current: 4 A, Output voltage: 230 V~, Rated power: 920 VA

Protection class (Device): IP 20, Temperature range (Device): -5 °C to 45 °C,

Dimensions: (L x W x D): 71 mm x 71 mm x 45 mm, Mounting depth: 32 mm,

Programming only with bus voltage applied via the web interface of the System Access Point., Additional information about commissioning and operation is contained in the system manual and the online operating manual of the current Online-Catalogue.

Order Code : 2CKA006220A0128

Article No. : SBA-F-1.1.1

EAN: 4011395180167