PROXIMA LED

BULKHEADS

CHARACTERISTIC

Supply voltage:	230V
Frequency:	50Hz
Ingress protection IP:	IP65/IP54
Impact resistance IK:	IK10
Energy efficiency class:	EEI=A
Electrical protection class:	I
Material of the body:	PP
Colour temperature:	3000K, 4000K
Mounting version:	Surface
Material of the diffuser:	PC
Type of the diffuser:	Opal
Light source:	LED GO!

SPECIFICATION

Surface mounted, round LED light fitting with a high luminous flux, high protection class IP65/IP54 and an integrated energy-saving light source LED GO!. Base and ring made of UV-resistant plastic. Specially formed diffuser made of impact resistant PC ensures the highest impact resistance of the fitting (IK10). Available in two ring colours: white and silver; optional equipment: radio motion sensor (RCR). Colour temperature 3000K/4000K, CRI>80, lifespan of LED 50.000h (L70@25°C).

APPLICATION

Luminaire suited for surface mounting on ceilings or walls, intended for outdoor (facade lighting) or indoor use (rooms with high humidity, passageways). Available option with a radio motion sensor (RCR). Particularly well suited for passageways and usable rooms. The luminaire will also work well as a general light source due to the decorative effect that it provides (indirect light distribution on the mounting surface). Two ring colours available: white or silver.

PROXIMA LED

BULKHEADS

AVAILABLE OPTIONS

Click on index to go to detailed catalogue extract

Index	Rated power	Colour temperature	Luminous flux **	Material of the diffuser	Type of the diffuser	RCR / PIR	Energy efficiency class
» 311420/PA	24W	4000K	2300lm	PC	Opal		A
» 311437/PA	24W	4000K	2300lm	PC	Opal	RCR	A
» 311949/PA	24W	3000K	2150lm	PC	Opal	RCR	A
» 311918/PA	24W	4000K	2300lm	PC	Opal	RCR	A
» 311956/PA	24W	3000K	2150lm	PC	Opal	RCR	A
» 311925/PA	24W	4000K	2300lm	PC	Opal	RCR	A
» 311413/PA	24W	3000K	2150lm	PC	Opal		A
» 311406/PA	24W	3000K	2150lm	PC	Opal		A
» 546310/HV	20W	3000K	1300lm	PC	Opal	RCR	A
» 546297/HV	20W	4000K	1450lm	PC	Opal		A
» 546358/HV	20W	3000K	1300lm	PC	Opal		A
» 546327/HV	20W	3000K	1300lm	PC	Opal	RCR	A
» 546303/HV	20W	4000K	1450lm	PC	Opal		A
» 546365/HV	20W	3000K	1300lm	PC	Opal		A
» 546341/HV	20W	4000K	1450lm	PC	Opal	RCR	A
» 311406/OSRAM	16W	3000K	1120lm	PC	Opal		A
» 310874/OSRAM	16W	3000K	1120lm	PC	Opal		A
» 310867/OSRAM	16W	4000K	1210lm	PC	Opal		A
» 546464/OSRAM	16W	3000K	1120lm	PC	Opal	RCR	A

** Initial, tolerance +/- 10%

The company reserves the right to make design changes or upgrades in the presented product.
Product data sheet does not constitute an offer.

Revision date: 2017-07-27

Lena Lighting S.A.
ul. Kornicka 52
63-000 Sroda Wielkopolska

tel. +48 (61) 28 60 300
fax.+48 (61) 28 54 059
e-mail: office@lenalighting.pl
www.lenalighting.pl

The luminaire complies with the EU ROHS Directive 2011/65/UE.

This product is a subject to electric and electronic waste equipment regulations (WEEE).

62/2013