



Main

Range of product	Sedna
Product or component type	Socket-outlet
Device presentation	Without frame
Outlet poles configuration	2P + E with shutters
Outlet standard description	Side earth
Rated current	16 A - 250 V AC
Cover plate colour tint	Aluminium
Connections - terminals	Lift terminals

Complementary

Wiring device mounting	Flush
Power range	3680 W
Number of cables	2 x 2.5 mm ²
Cable stiffness	Flexible Rigid
Wire stripping length	12 mm
Material	ASA + PC
Surface finish	Glossy
Fixing mode	Claws, span of claws working range : 54...71 mm Screws
Height	71 mm
Width	71 mm
Depth	44.6 mm
Projecting depth	14.5 mm
Product weight	0.07568 kg

Environment

Standards	IEC 60884-1
Product certifications	GOST-R
IP degree of protection	IP20

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 1715 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold
Product environmental profile	Available Product environmental
Product end of life instructions	Need no specific recycling operations

Contractual warranty

Warranty period	18 months
-----------------	-----------