

DELTA pushbutton device insert, UP 1 NO, 10A 250V



Model	
Product brand name	DELTA
Product designation	Pushbutton insert
Design of the product	single pushbutton
Design of the switching function	1 NO contact
Type of composition	basic element
Design of the operating mechanism	pushbutton/momentary pushbutton
General technical data	
Printed marking	Without
Mounting type	fixing with claw and screw
Surface processing	others
Material	others
Protection class	
Protection class IP	IP20
Switching capacity	
Switching capacity current	10 A
Main circuit	

Operating voltage / Rated value	250 V
Operating current / rated value	10 A

Appearance

Appearance	not applicable
Color	miscellaneous

Product details

Product component	
<ul style="list-style-type: none"> • Labeling field • Integrated / Light source • Signaling contact 	<p>No</p> <p>No</p> <p>No</p>
Product feature	
<ul style="list-style-type: none"> • halogen-free • transparent 	<p>Yes</p> <p>No</p>

Number

Number of actuating rockers	1
-----------------------------	---

Mechanical Design

Height	70 mm
Width	70 mm
Depth	32 mm
Mounting type	flush mounted
Material / of the enclosure	metal

General Product Approval

Declaration of Conformity

Test Certificates



CCC



ÖVE



VDE



EG-Konf.

[Miscellaneous](#)

[Type Test Certificates/Test Report](#)

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=5TD2120>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/5TD2120>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=5TD2120

CAX-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

<http://www.siemens.com/specifications>

