

Products → Low Voltage Products and Systems → Control Products → Contactors → Block Contactors Accessories

## General Information

<b>Extended Product Type:</b>	VE5-1
<b>Product ID:</b>	1SBN030110R1000
<b>EAN:</b>	3471522121370
<b>Catalog Description:</b>	VE5-1 Block Contactor Accessories
<b>Long Description:</b>	VE5-1 Block Contactor Accessories

## Ordering

<b>EAN:</b>	3471522121370
<b>Minimum Order Quantity:</b>	1 piece
<b>Customs Tariff Number:</b>	85389099

## Dimensions

<b>Product Net Weight:</b>	0.076 kg
----------------------------	----------

## Container Information

<b>Package Level 1 Units:</b>	1 piece
<b>Package Level 1 Gross Weight:</b>	0.076 kg
<b>Package Level 1 EAN:</b>	3471522121370
<b>Package Level 2 Units:</b>	90 piece

## Environmental

<b>RoHS Status:</b>	Following EU Directive 2002/95/EC August 18, 2005 and amendment
---------------------	---

## Additional Information

<b>Conventional Free-air Thermal Current (<math>I_{th}</math>):</b>	acc. to IEC 60947-5-1, $q = 40\text{ °C}$ 16.0 A
<b>Mechanical Durability:</b>	5 million
<b>Mounted Auxiliary Contacts:</b>	0 NO, 2 NC
<b>Mounting on Contactors:</b>	A 9 ...A 40, N
<b>Mounting Type:</b>	rail or plate not supplied
<b>Number of Auxiliary Contacts NC:</b>	2
<b>Order Multiple:</b>	1 piece
<b>Power Loss:</b>	at Rated Operating Conditions per Pole 0.1 W
<b>Product Main Type:</b>	Accessories for Block Contactors
<b>Product Name:</b>	Block Contactor Accessories

<b>Rated Breaking Capacity acc. to IEC 60947-5-1:</b>	10 x I <sub>e</sub> AC-15
<b>Rated Frequency (f):</b>	Supply Circuit 50 Hz Supply Circuit 60 Hz
<b>Rated Insulation Voltage (U<sub>i</sub>):</b>	acc. to IEC 60947-5-1 and VDE 0110 (Gr. C) 690 V acc. to UL/CSA 600 V
<b>Rated Making Capacity acc. to IEC 60947-5-1:</b>	10 x I <sub>e</sub> AC-15
<b>Rated Operational Current AC-15 (I<sub>e</sub>):</b>	(220 / 240 V) 4 A (24 / 127 V) 6 A (380 / 440 V) 3 A (500 V) 2 A (690 V) 2 A
<b>Rated Operational Current DC-13 (I<sub>e</sub>):</b>	(125 V) 0.55 A (24 V) 6 A (250 V) 0.3 A (48 V) 2.8 A (72 V) 1 A
<b>Rated Operational Voltage:</b>	Auxiliary Circuit 690 V
<b>Rated Short-time Withstand Current (I<sub>cw</sub>):</b>	for 0.1 s 140.0 A for 1 s 100 A
<b>Suitable For:</b>	AX06 AX09 AX12 AX18 AX25 AX32 AX40
<b>Terminal Type:</b>	Screw Terminals
<b>Version:</b>	Mechanical/Electrical

## Certificates and Declarations (Document Number)

<b>CB Certificate:</b>	CB_CN_37804
<b>CCC Certificate:</b>	CCC_2016010304881659
<b>Data Sheet, Technical Information:</b>	1SBC100122C0202_Ch04
<b>Declaration of Conformity - CE:</b>	1SBD250814U1000
<b>Environmental Information:</b>	1SBD250146E1000
<b>GOST Certificate:</b>	GOST_POCCFRME77B07175
<b>Instructions and Manuals:</b>	FPTC407718P0001
<b>RINA Certificate:</b>	RINA_ELE128713XG001
<b>RoHS Information:</b>	1SBC101061D0201

## Classifications

<b>E-nummer:</b>	3228825
<b>ETIM 4:</b>	EC002498 - Accessories for low-voltage switch technology
<b>ETIM 5:</b>	EC002498 - Accessories for low-voltage switch technology
<b>ETIM 6:</b>	EC002498 - Accessories for low-voltage switch technology
<b>UNSPSC:</b>	39120000

