## Product data sheet Characteristics

## CCT99100 Universal LED dimmer module





## Main

Range	Merten	
Product name	Merten inserts	
Product or component type	Dimmer	
Device presentation	Complete device	

## Complementary

		<u>.</u>
Mounting support	Flush	<u>-</u>
Control type	With mechanical push-button	
Device application	Automatic load detection	
[Ue] rated operational voltage	230 V AC 50 Hz	
Load type	LED lamp : 420 VA (RL LED mode) LED lamp : 4100 VA (RC mode) Low voltage halogen lamp with ferromagnetic transformer : 5200 VA Low voltage halogen lamp with electronic transformer : 5200 W Halogen lamp : 5150 W at 230 V Incandescent lamp : 5200 W	to be used for determin
Protection type	Overheating protection Electronic short-circuit and automatic overload protection	<u>is</u>
Wire stripping length	6 mm	
Connections - terminals	Screw terminals : 1 x 2.5 mm² (solid) Screw terminals : 1 x 2.5 mm² (rigid)	
Relative humidity	595 %	
IP degree of protection	IP20	
Standards	EN 60669-2-1 EN 61000-6-3	i to
Product certifications	CE	<u></u> .g
Type of packing	Carton	t to
Height	45 mm	<u> </u>
Width	40 mm	<u>ئ</u> ن ب <u>ت</u>
Depth	20 mm	
Embedding depth	20 mm	 

Product weight	0.02 kg	
Offer Sustainability		
Sustainable offer status	Green Premium product	
RoHS (date code: YYWW)	Compliant - since 1532 - Schneider Electric declaration of conformity	

Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold

Available

Available

REACh

Product environmental profile

Product end of life instructions