



Main

Range of product	Sedna
Product or component type	USB charger
Integrated connection type	2 USB 2.0 port 5 V DC, maximum load current: 2.1 A

Complementary

Device application	Charger
Device mounting	Flush
Device presentation	Mechanism with central plate
Colour tint	Cream
Surface treatment	Untreated
Fixing mode	By claws By screws
Type of packing	Flow-pack
[Ue] rated operational voltage	100...240 V (+/- 10 %) AC 50/60 Hz
Power consumption in W	<= 0.1 W
Nominal output power	10.5 W
Input power	12 W
Service life in hours	30000 h 10.5 W
Material	PC (polycarbonate) GF10 FR for casing ABS (acrylonitrile butadiene-styrene) for centre plate PC (polycarbonate) GF10 FR for internal cover
Protection type	Short-circuit protection
Number of terminals	2 screw terminals
Clamping connection capacity	2 x 0.75...2 x 2.5 mm ² (flexible) 2 x 0.75...2 x 2.5 mm ² (rigid) 2 x 0.75...2 x 2.5 mm ² (stranded)
Wire stripping length	8 mm
Product compatibility	Mobile/Tablet Android Mobile/Tablet Mac iOS Mobile/Tablet Windows
Height	71 mm
Width	71 mm
Depth	37 mm

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Embedding depth	30.8 mm
-----------------	---------

Environment

Ambient air temperature for operation	0...40 °C
Ambient air temperature for storage	-5...50 °C
Standards	EN 60950-1 EN 62684 ETSI EN 301 489-4
Directives	2004/108/EC - electromagnetic compatibility 2006/95/EC - low voltage directive 2002/96/EC - WEEE directive 2002/95/EC - RoHS directive
Product certifications	EAC
Electrical insulation class	Class II
IK degree of protection	IK04
IP degree of protection	IP20
Environmental characteristic	REACH Regulation (EC) No 1907/2006

Offer Sustainability

Product environmental profile	Available
Product end of life instructions	Need no specific recycling operations