# NUMINOS® MOVE S

**black recessed ceiling light, 4000K 55°**

The NUMINOS light system from SLV combines technology, design and functionality like no other. With different downlights and spotlights, you provide a thousand lighting design possibilities. Also with the NUMINOS® MOVE S recessed ceiling light, which convinces with the best workmanship and lighting quality. Ideal for harmonious, modern and space-saving lighting that directs the accent to objects or the room. This means that easy installation is a mere formality. When will you choose SLV's modular variety?




## TECHNICAL DATA

| | |
|---|---|
| **Item no.:** | 1005361 |
| **Number of different light outlets** | 1 |
| **Secondary power / secondary voltage** | 250mA |
| **Height** | 6.35 cm |
| **Diameter** | 10 cm |
| **Installation diameter** | 9 cm |
| **Installation depth** | 8.5 cm |
| **Net weight** | 0.19 kg |
| **Gross weight** | 0.203 kg |
| **IP Code** | IP 20 |
| **Safety class** | III |
| **Impact resistance class** | IK02 |
| **Impact resistance** | 0,2 Joule |
| **Assembly** | Recessed |
| **Assembly details** | Ceiling |
| **Wattage** | 8.6 W |
| **Lumen** | 730 lm |
| **Colour temperature** | 4000 Kelvin |
| **Beam angle** | 55 ° |
| **Color** | black |
| **CRI** | 90 |
| **UGR ≤** | 22 |

## Light Source

| | |
|---|---|
| 791831 | E |

## Accessories

| | |
|---|---|
| 1004055 | LED driver , 6.5-10W 250mA PHASE |
| 1004058 | LED driver , 6.5-10W 250mA |
| 1004067 | LED driver , 15W 250mA DALI |
| 1004786 | NUMINOS® S , diffuser Ellipse |
| 1004787 | NUMINOS® S , diffuser Prisma |
| 1004788 | NUMINOS® S , diffuser Frosted |
| 1004789 | NUMINOS® S , diffuser Wabe |
| 1006139 | Numinos® S Reducing ring , round 160/100mm black |
| 1006140 | Numinos® S Reducing ring , round 160/100mm white |
| 1006141 | Numinos® S Reducing ring , square 160/100mm black |
| 1006142 | Numinos® S Reducing ring , square 160/100mm white |

| | |
|---|---|
| **LXXBXX data** | L80B50 |
| **Service life** | 50000 h |
| **Minimum ambient temperature** | -20 °C |
| **Maximum ambient temperature** | 40 °C |
| **BIG WHITE Page** | 41 |