


## MILANDOS 8

black recessed ceiling light, 3000K 45°

Minimalist, innovative and compact in design, the MILANDOS recessed ceiling light creates high-quality lighting. The true-to-life colour reproduction index of over 90 and the long LED lifespan of 60,000 hours also speak for the light. With a UGR of 16, it produces glare-free light. The simple design of the recessed ceiling light made of aluminium and polycarbonate (PC) blends seamlessly into any room. The spotlight is also quick and easy to install. When will you test out the benefits of SLV's impressive indoor lights?



## TECHNICAL DATA

Item no.:	1005424
Secondary power / secondary voltage	700mA
Length	25.6 cm
Width	5.6 cm
Height	4.3 cm
Installation length	25 cm
Installation width	4.9 cm
Installation depth	7 cm
Net weight	0.4 kg
Gross weight	0.428 kg
IP Code	IP 20
Safety class	III
Impact resistance class	IK02
Assembly	Recessed
Assembly details	Ceiling
Lumen	1040 lm
Colour temperature	3000 Kelvin
Beam angle	45 °
Color	black
CRI	90
UGR ≤	16
LXXBXX data	L80B50

## Light Source

1078215	
---------	---

## Accessories

1002423	LED driver MEDO 300 , dimmable DALI/1-10V
1006202	LED Driver , 20W 700mA

Service life	60000 h
Ambient temperature	30 °C
BIG WHITE Page	349