






## MILANDOS 6

## black recessed ceiling light, 3000K $45^{\circ}$

Minimalist, innovative and compact in design, the MILANDOS recessed ceiling light creates high-quality lighting. The long LED lifespan of 60,000 hours and the high colour reproduction index of over 90 are also convincing across the board. With a UGR of 16, it produces glare-free light. The simple design of the recessed ceiling light made of aluminium and polycarbonate (PC) blends seamlessly into any room. The spotlight is also quick and easy to install. Experience MILANDOS in action and convince yourself of a successful lighting experience.



## **TECHNICAL DATA**

Item no.:	1005416
Secondary power / secondary volta- ge	700mA
Length	19.6 cm
Width	5.6 cm
Height	4.3 cm
Installation length	19 cm
Installation width	4.9 cm
Installation depth	7 cm
Net weight	0.3 kg
Gross weight	0.321 kg
IP Code	IP 20
Safety class	III
Impact resistance class	IK02
Assembly	Recessed
Assembly details	Ceiling
Lumen	780 lm
Colour temperature	3000 Kelvin
Beam angle	45 °
Color	black
CRI	90
UGR≤	16
LXXBXX data	L80B50
	-



## **Light Source**

1078215	A E
Accessories	
1002423	LED driver MEDO 300 , dimmable DALI/1-10V
464147	LED Driver 14.7W 700- mA dimmable

Service life	60000 h
Ambient temperature	30 °C
BIG WHITE Page	349