




NUMINOS® XL PHASE

black pendant light, 36W 2700K 24°

The NUMINOS light system from SLV perfectly combines function, design and technology. With different downlights and spotlights, you can experience a thousand lighting design possibilities. Like with the NUMINOS® XL PHASE pendant light, which impresses with its high-quality workmanship and light. In this way, you can create high-quality illumination of larger areas or use the spotlight for selective lighting. The pendant light has a power consumption of 36 watts, a luminous flux of 3290 lumens, a colour temperature of 2700 Kelvin and a good colour reproduction index of over 90. Installation is then done in no time at all. When to choose NUMINOS from SLV – modular diversity awaits you.



TECHNICAL DATA

| | |
|-------------------------------------|------------------------|
| Item no.: | 1005705 |
| Number of different light outlets | 1 |
| Primary nominal voltage | 220-240V ~50/60Hz mA/V |
| Secondary power / secondary voltage | 900mA |
| Pendant length | 250 cm |
| Height | 25.8 cm |
| Diameter | 12 cm |
| Net weight | 1.745 kg |
| Gross weight | 1.867 kg |
| Safety class | I |
| Assembly | Surface |
| Assembly details | Ceiling |
| Dimmable | Yes |
| Dimming technology | trailing edge |
| Wattage | 36 W |
| Lumen | 3290 lm |
| Colour temperature | 2700 Kelvin |
| Beam angle | 24 ° |
| Color | black |
| CRI | 90 |
| UGR ≤ | 19 |
| BIG WHITE Page | 95 |

Light Source

| | |
|--------|-----------------------------------------------------------------------------------|
| 791857 |  |
|--------|-----------------------------------------------------------------------------------|

Accessories

| | |
|---------|-----------------------------------|
| 1006170 | NUMINOS® XL , white front ring |
|---------|-----------------------------------|