




## NUMINOS® MOVE DL L

Indoor LED recessed ceiling light black/white 3000K  
20° rotating and pivoting

The NUMINOS light system from SLV combines technology, design and functionality like no other. With various downlights and spotlights, you provide a thousand lighting design options. This also includes NUMINOS® MOVE DL L, which impresses as a recessed ceiling light with the best workmanship and lighting quality. In this way, you can create discreet, modern and space-saving lighting that draws the focus to objects or the room. The recessed ceiling light can convince with a power consumption of 25.41 watts, luminous flux of 2300 lumens, colour temperature of 3000 Kelvin and a high colour reproduction index of over 90. Installation is then done in no time at all. When do you choose NUMINOS ® from SLV?



## TECHNICAL DATA

Item no.:	1003650
Number of different light outlets	1
Secondary power / secondary voltage	700mA
Height	9.5 cm
Diameter	16 cm
Installation diameter	14.5 cm
Installation depth	10.5 cm
Net weight	0.49 kg
Gross weight	0.524 kg
IP Code	IP 20
Safety class	III
Impact resistance class	IK02
Impact resistance	0,2 Joule
Assembly	Recessed
Assembly details	Ceiling
Wattage	25.41 W
Lumen	2300 lm
Colour temperature	3000 Kelvin
Beam angle	20 °
Color	black
CRI	90
UGR ≤	19

## Light Source

791822	
--------	---

## Accessories

1004062	LED driver , 21-29.5W 500/600/700mA
1004065	LED driver , 30W 700mA
1004070	LED driver , 40W 700mA
1004794	NUMINOS® L , diffuser Ellipse
1004795	NUMINOS® L , diffuser Prisma
1004796	NUMINOS® L , diffuser Frosted
1004797	NUMINOS® L , diffuser Wabe
1006147	Numinos® L Reducing ring , round 240/150mm black
1006148	Numinos® L Reducing ring , round 240/150mm white
1006149	Numinos® L Reducing ring , square 240/150mm black
1006150	Numinos® L Reducing ring , square 240/150mm white

LXXBXX data	L80B50
Service life	50000 h
Minimum ambient temperature	-20 °C
Maximum ambient temperature	40 °C
BIG WHITE Page	44