




NUMINOS® DL S

Indoor LED recessed ceiling light white/black 2700K
20° gimballed, rotating and pivoting, including leaf
springs

The NUMINOS light system from SLV combines technology, design and functionality like no other. This way, you can experience a thousand lighting design possibilities with different downlights and spotlights. This also includes NUMINOS® DL S, which impresses as a recessed ceiling light with the best workmanship and lighting quality. In this way, you can create unobtrusive, modern and space-saving lighting that draws the focus to objects or the room. The recessed ceiling light has a power consumption of 8.6 watts, a luminous flux of 670 lumens, a colour temperature of 2700 Kelvin and a good colour reproduction index of over 90. This means that easy installation is a mere formality. When will you choose SLV's modular variety?



TECHNICAL DATA

| | |
|-------------------------------------|---------------|
| Item no.: | 1003781 |
| Number of different light outlets | 1 |
| Secondary power / secondary voltage | 250mA |
| Height | 5.2 cm |
| Diameter | 8 cm |
| Installation diameter | 6.8 cm |
| Installation depth | 5.5 cm |
| Net weight | 0.16 kg |
| Gross weight | 0.2 kg |
| IP Code | IP 20 / IP 44 |
| Safety class | III |
| Impact resistance class | IK02 |
| Impact resistance | 0,2 Joule |
| Assembly | Recessed |
| Assembly details | Ceiling |
| Wattage | 8.6 W |
| Lumen | 670 lm |
| Colour temperature | 2700 Kelvin |
| Beam angle | 20 ° |
| Color | white |
| CRI | 90 |
| UGR ≤ | 19 |

Light Source

| | |
|--------|-----------------------------------------------------------------------------------|
| 791819 |  |
|--------|-----------------------------------------------------------------------------------|

Accessories

| | |
|---------|---------------------------------------------------------|
| 1004055 | LED driver , 6.5-10W 250mA PHASE |
| 1004058 | LED driver , 6.5-10W 250mA |
| 1004067 | LED driver , 15W 250mA DALI |
| 1004786 | NUMINOS® S , diffuser Ellipse |
| 1004787 | NUMINOS® S , diffuser Prisma |
| 1004788 | NUMINOS® S , diffuser Frosted |
| 1004789 | NUMINOS® S , diffuser Wabe |
| 1006135 | Numinos® XS Reducing ring , round 160/70mm black |
| 1006136 | Numinos® XS Reducing ring , round 160/70mm white |
| 1006137 | Numinos® XS Reducing ring , square 160/70mm black |
| 1006138 | Numinos® XS Reducing ring , square 160/70mm white |

| | |
|-----------------------------|---------|
| LXXBXX data | L80B50 |
| Service life | 50000 h |
| Minimum ambient temperature | -20 °C |
| Maximum ambient temperature | 40 °C |
| BIG WHITE Page | 31 |