




NUMINOS® DL L

Indoor LED recessed ceiling light white/white 4000K 40°

The NUMINOS light system from SLV skilfully combines function, design and technology. With various downlights and spotlights, you provide a thousand lighting design options. Like with the NUMINOS® DL L recessed ceiling light, which impresses with its high-quality workmanship and light. Ideal for discreet, modern and space-saving lighting that draws the focus to objects or the room. The recessed ceiling light convinces with a power consumption of 25.41 watts, luminous flux of 2450 lumens, colour temperature of 4000 Kelvin and a colour reproduction index of 90. Installation is then done in no time at all. When do you choose NUMINOS ® from SLV?



TECHNICAL DATA

Item no.:	1003977
Number of different light outlets	1
Secondary power / secondary voltage	700mA
Height	8.5 cm
Diameter	13 cm
Installation diameter	11.7 cm
Installation depth	9 cm
Net weight	0.465 kg
Gross weight	0.525 kg
IP Code	IP 20 / IP 44
Safety class	III
Impact resistance class	IK02
Impact resistance	0,2 Joule
Assembly	Recessed
Assembly details	Ceiling
Wattage	25.41 W
Lumen	2450 lm
Colour temperature	4000 Kelvin
Beam angle	40 °
Color	white
CRI	90
UGR ≤	19

Light Source

791825	
--------	---

Accessories

1004062	LED driver , 21-29.5W 500/600/700mA
1004065	LED driver , 30W 700mA
1004070	LED driver , 40W 700mA
1004794	NUMINOS® L , diffuser Ellipse
1004795	NUMINOS® L , diffuser Prisma
1004796	NUMINOS® L , diffuser Frosted
1004797	NUMINOS® L , diffuser Wabe
1006143	Numinos® M Reducing ring , round 240/120mm black
1006144	Numinos® M Reducing ring , round 240/120mm white
1006145	Numinos® M Reducing ring , square 240/120mm black
1006146	Numinos® M Reducing ring , square 240/120mm white

LXXBXX data	L80B50
Service life	50000 h
Minimum ambient temperature	-20 °C
Maximum ambient temperature	40 °C
BIG WHITE Page	34