




3~ NUMINOS® PHASE M

3 phase system light white/black 2700K 60°

The NUMINOS light system from SLV perfectly combines function, design and technology. With different downlights and spotlights, you can experience a thousand lighting design possibilities. Like with the 3~ NUMINOS® PHASE M 3-phase system light LED, which impresses with its high-quality workmanship and light. In this way, you can create high-quality illumination of larger areas or use the spotlight for selective lighting. The recessed ceiling light convinces with a power consumption of 20.1 watts, luminous flux of 1885 lumens, colour temperature of 2700 Kelvin and a colour reproduction index of 90. Installation is then done in no time at all. When do you choose NUMINOS ® from SLV?



TECHNICAL DATA

Item no.:	1004176
Primary nominal voltage	220-240V ~50/60Hz mA/V
Secondary power / secondary voltage	500mA
Length	18.5 cm
Height	16.5 cm
Diameter	8.5 cm
Net weight	0.77 kg
Gross weight	1.06 kg
Safety class	I
Assembly details	Track Ceiling
Dimmable	Yes
Dimming technology	trailing edge
Wattage	20.1 W
Lumen	1885 lm
Colour temperature	2700 Kelvin
Beam angle	60 °
Color	white
CRI	90
UGR ≤	22
LXXBXX data	L80B50
Service life	50000 h
BIG WHITE Page	64

Light Source

791800	
--------	---

Accessories

1006168	NUMINOS® M , white front ring
---------	-------------------------------