


## NUMINOS® CL PHASE M

Indoor LED surface ceiling light black/black 3000K 36°

The NUMINOS light system from SLV combines technology, design and functionality like no other. With various downlights and spotlights, you can experience a thousand lighting design possibilities. Like with the NUMINOS® CL PHASE M indoor ceiling-mounted light LED, which impresses with its high-quality workmanship and light. With the spotlight, you can opt for spot lighting or high-quality illumination of larger areas. The recessed ceiling light convinces with a power consumption of 20.1 watts, luminous flux of 1970 lumens, colour temperature of 3000 Kelvin and a colour reproduction index of 90. This means that easy installation is a mere formality. When to choose NUMINOS from SLV – modular diversity awaits you.



## TECHNICAL DATA

|                                     |                        |
|-------------------------------------|------------------------|
| Item no.:                           | 1004227                |
| Primary nominal voltage             | 220-240V ~50/60Hz mA/V |
| Secondary power / secondary voltage | 500mA                  |
| Height                              | 18.5 cm                |
| Diameter                            | 8.5 cm                 |
| Net weight                          | 0.68 kg                |
| Gross weight                        | 0.93 kg                |
| Safety class                        | I                      |
| Assembly                            | Surface                |
| Assembly details                    | Ceiling                |
| Dimmable                            | Yes                    |
| Dimming technology                  | trailing edge          |
| Wattage                             | 20.1 W                 |
| Lumen                               | 1970 lm                |
| Colour temperature                  | 3000 Kelvin            |
| Beam angle                          | 36 °                   |
| Color                               | black                  |
| CRI                                 | 90                     |
| UGR ≤                               | 13                     |
| LXXBXX data                         | L80B50                 |
| Service life                        | 50000 h                |
| BIG WHITE Page                      | 82                     |

## Light Source

|        |   |
|--------|---|
| 791822 |  |
|--------|---|

## Accessories

|         |                               |
|---------|-------------------------------|
| 1006168 | NUMINOS® M , white front ring |
|---------|-------------------------------|