




NUMINOS® PD PHASE L

Indoor LED pendant light black/black 3000K 36°

The NUMINOS light system from SLV combines technology, design and functionality like no other. With various downlights and spotlights, you provide a thousand lighting design options. Also with the NUMINOS® PD PHASE L pendant light, which convinces with the best workmanship and lighting quality. With the spotlight, you can opt for spot lighting or high-quality illumination of larger areas. The recessed ceiling light convinces with a power consumption of 28 watts, luminous flux of 2340 lumens, colour temperature of 3000 Kelvin and a colour reproduction index of 90. Installation is then done in no time at all. When to choose NUMINOS from SLV – modular diversity awaits you.



TECHNICAL DATA

| | |
|-------------------------------------|---------------------------|
| Item no.: | 1004351 |
| Primary nominal voltage | 220-240V ~50/60Hz mA/V |
| Secondary power / secondary voltage | 700mA |
| Pendant length | 250 cm |
| Height | 21.3 cm |
| Diameter | 10 cm |
| Net weight | 1.234 kg |
| Gross weight | 1.543 kg |
| Safety class | I |
| Assembly | Surface |
| Assembly details | Ceiling,Ceiling with Acc. |
| Dimmable | Yes |
| Dimming technology | trailing edge |
| Wattage | 28 W |
| Lumen | 2340 lm |
| Colour temperature | 3000 Kelvin |
| Beam angle | 36 ° |
| Color | white |
| CRI | 90 |
| UGR ≤ | 13 |
| LXXBXX data | L80B50 |
| Service life | 50000 h |

Light Source

| | | | |
|--------|---|----------------|----|
| 791822 |  | BIG WHITE Page | 92 |
|--------|---|----------------|----|

Accessories

| | |
|---------|-------------------------------|
| 1006169 | NUMINOS® L , white front ring |
|---------|-------------------------------|