




LED PANEL 600x600

Indoor LED recessed ceiling light white 3000K
UGR<19

The LED PANEL 600 comes in several different light colours for grid ceilings and provides a modern and space-saving solution for an efficient kind of base lighting. You achieve a pleasant, homogeneous and glare-free lighting sensation with this product, with an aperture angle of less than 19°.



TECHNICAL DATA

Item no.:	1003083
Secondary power / secondary voltage	1050mA
Length	59.5 cm
Width	59.5 cm
Height	0.9 cm
Installation depth	5 cm
Net weight	2.924 kg
Gross weight	3.51 kg
IP Code	IP 20
Safety class	III
Assembly	Recessed
Assembly details	Ceiling, Ceiling with Acc.
Lumen	4000 lm
Colour temperature	3000 Kelvin
Beam angle	120 °
Color	white
CRI	90
UGR ≤	19
LXXBXX data	L70B50
Service life	50000 h
BIG WHITE Page	419

Light Source

916527	
--------	---

Accessories

1002425	LED driver MEDO 600 , dimmable DALI/1-10V
158791	CEILING PLATE , for LED PANEL, I-VIDUAL and I-VIDUAL LED PA- NEL, white
158799	SUSPENSION SET , for LED PANEL, I-VIDUAL and I-VIDUAL LED PA- NEL, steel wire and Y-wire suspension
464804	LED DRIVER , 40W, 1050mA, triac dimmable