


## **FLATT**

## Outdoor LED surface-mounted wall light 3000K IP65 anthracite/brown

Would you like a wall light which can be fitted effortlessly? This should have a safety class of at least IP 65, and therefore be thus dustproof and protected from water spray from various directions. Our FLATT WL has IP 65 and is suitable for providing a surface, path or terrace with fantastic illumination. Are you looking for amazing light for your outdoor area? This is provided by the built-in Premium LED of the FLATT POLE 65 floor stand. Incidentally, the FLATT POLE 65 gives you even more advantages as a part of the SLV family. Because we have been successful with our lighting concepts for 40 years, and keep setting the bar higher for ourselves and our products.




## **TECHNICAL DATA**

|                                     | Т                      |
|-------------------------------------|------------------------|
| Item no.:                           | 1002953                |
| Primary nominal voltage             | 100-277V ~50/60Hz mA/V |
| Secondary power / secondary voltage | 300mA                  |
| Width                               | 18 cm                  |
| Height                              | 23 cm                  |
| Depth                               | 7 cm                   |
| Net weight                          | 2.013 kg               |
| Gross weight                        | 2.284 kg               |
| IP Code                             | IP 65                  |
| Safety class                        | I                      |
| Impact resistance class             | IK03                   |
| Impact resistance                   | 0,35 Joule             |
| Assembly                            | Surface                |
| Assembly details                    | Wall                   |
| Wattage                             | 14 W                   |
| Lumen                               | 500 lm                 |
| Colour temperature                  | 3000/4000 Kelvin       |
| Color                               | brown                  |
| CRI                                 | 80                     |
| LXXBXX data                         | L70B50                 |
| Service life                        | 54000 h                |
| Ambient temperature                 | 40 °C                  |
|                                     | -                      |



## **Light Source**



| Minimum ambient temperature | -25 °C |
|-----------------------------|--------|
| Maximum ambient temperature | 40 °C  |
| BIG WHITE Page              | 640    |