



## IMPERVA 150 CW


LED Outdoor wall and ceiling light, IP66, grey, 4000K

The functional wall and ceiling light has a diffuser which creates a pleasant light distribution. The luminaire was designed with powerful LEDs and is available in several lengths. The IP luminaire can be fitted with a warm white or cool white LEDs as required. Thanks to the built-in ballast, the luminaire is ready for direct connection to the 230V mains voltage supply.

### TECHNICAL DATA

Item no.:	1001317
Primary nominal voltage	220-240V ~50/60Hz mA/V
Secondary power / secondary voltage	1050mA
Length	156 cm
Width	12 cm
Height	10.8 cm
Net weight	3.002 kg
Gross weight	3.374 kg
IP Code	IP 66
Safety class	I
Impact resistance class	IK08
Assembly	Surface
Assembly details	Ceiling, Wall
Number of through-wires	30
Wattage	55 W
Lumen	7600 lm
Colour temperature	4000 Kelvin
Beam angle	120 °
Color	grey
CRI	80
LXXBXX data	L70B50
Service life	50000 h

## Light Source

916445		<b>Minimum ambient temperature</b>	-20 °C
		<b>Maximum ambient temperature</b>	40 °C
		<b>BIG WHITE Page</b>	692