


MEDO 30 EL

LED indoor recessed ceiling light, frame version, white, 3000/4000K

The MEDO FRAME variants round off the recessed lights in the MEDO series. The MEDO FRAME lights blend into any room perfectly, just like the frameless versions. Understated yet still powerful, they provide bright illumination. Supplemented by an additional driver, the TRIAC recessed variant becomes dimmable and can be integrated in DALI systems.



TECHNICAL DATA

Item no.:	1001905
Secondary power / secondary voltage	350mA
Height	10.1 cm
Diameter	30 cm
Installation diameter	29 cm
Installation depth	13 cm
Net weight	1.6 kg
Gross weight	2.097 kg
IP Code	IP 20
Safety class	III
Assembly	Recessed
Assembly details	Ceiling
Wattage	14 W
Lumen	1600 lm
Colour temperature	3000/4000 Kelvin
Beam angle	105 °
Color	white
CRI	90
UGR ≤	25
LXXBXX data	L70B50
Service life	25000 h
Maximum ambient temperature	40 °C

Light Source

916562		BIG WHITE Page	416
--------	---	----------------	-----

Accessories

1002232	LED driver , 350mA, 20-W, dimmable
1002423	LED driver MEDO 300 , dimmable DALI/1-10V