



## QR111 MODULE MOVE for AIXLIGHT PRO instal- lation frame

QR-LP111, matt white, max. 75W

The low-voltage QR111 MODULE MOVE to be mounted into installation housings, is available in either matt white or silver-grey finish. For precise adjustment of the light beam, the module can be extracted up to 5.5 cm from the housing which increases the swivel range. To operate the module inserts, a matching transformer with 12V AC is required.

### TECHNICAL DATA

Item no.:	115071
Socket	G53
Lamp	QR111
Number of sockets	1
Lamps included	No
Primary nominal voltage	12V ~50Hz mA/V
Tilt range	90 °
Horizontal rotation range	180 °
Net weight	0.468 kg
Gross weight	0.654 kg
IP Code	IP 20
Safety class	III
Wattage	75 W
Color	white

## Recommended lamp

560231	PHILIPS MASTER LED AR111 , CRI90, 15W, 24°, 2700K, dimmable
560232	PHILIPS MASTER LED AR111 , CRI90, 15W, 40°, 2700K, dimmable
560233	PHILIPS MASTER LED AR111 , CRI90, 15W, 24°, 3000K, dimmable
560234	PHILIPS MASTER LED AR111 , CRI90, 15W, 40°, 3000K, dimmable