

Product data sheet

Specifications



Fusarc CF, IND, 7.2 kV, 160 A, 292 mm

757352BP

Main

Range of product	Fusarc CF
Quality labels	ISO 14001 ISO 9001
Standards	IEC 60282-1 IEC 60787 DIN 43625 VDE 0670-402
Product or component type	Fuse
Protection technology	Current limiter Thermal limiter

Complementary

[In] rated current	160 A
Rated voltage (Ur)	7.2 kV
[Ue] rated operational voltage	3...7.2 kV
Maximum discharge current	50 kA
Braking current	1000 A
Average resistance	2.3 mOhm at 20 °C +/- 10 %
Power dissipation in W	87 W
Type of installation	Indoor
Material	Glass fiber
Product destination	Motor Power transformer Capacitor Voltage transformer
Condition of use	Cubicle In open air Fuse chamber
Length	292 mm
Net weight	3.4 kg
Diameter	86 mm

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1

Package 1 Weight	3.66 kg
Package 1 Height	9.5 cm
Package 1 width	9.5 cm
Package 1 Length	36 cm
Unit Type of Package 2	P12
Number of Units in Package 2	48
Package 2 Weight	177.12 kg
Package 2 Height	50 cm
Package 2 width	80 cm
Package 2 Length	120 cm