

## PRODUCT DATASHEET

### OT 100/220...240/24 DIM P

CV Power supplies 24 V with 1...10 V



#### AREAS OF APPLICATION

- Facades, public squares, cruise ships
- Signage
- Suitable for indoor and outdoor installations

#### PRODUCT FAMILY BENEFITS

- Large range of products from 20 W to 250 W
- Installation in very cold and hot environments
- Very stable output power
- High electrical reversible short-circuit, overload, overtemperature protection
- Smart Power Supply: boosting power to turn on cold LEDs
- Independent installation possible
- Dimming range: 1...100 %

#### PRODUCT FAMILY FEATURES


- DC mode functionality
- Type of protection: IP66 and IP67
- Surge protection: up to 4 kV (L-N) / 6 kV (L/N-PE)
- Wide operating temperature range: -30...+55 °C
- Lifetime: up to 50,000 h (temperature at max.  $t_c$ )
- Dimmable via fully isolated 1...10 V interface

**TECHNICAL DATA**

Electrical data

Nominal output power	100 W
Input voltage AC	198...264 V
Mains frequency	0...60 Hz
Nominal output voltage	24.2 V
Power loss in stand-by mode	<0.5 W
Nominal voltage	220...240 V
Device power loss	10 W
Power factor $\lambda$	0.95
ECG efficiency	90 %
Inrush current	60 A
Max. ECG no. on circuit breaker 10 A (B)	10
Max. ECG no. on circuit breaker 16 A (B)	16
Max. ECG no. on circuit breaker 25 A (B)	26
Galvanic isolation primary/secondary	3 kV
Surge capability (L/N-Ground)	6 kV
Surge capability (L-N)	4 kV

Dimensions & weight



Length	240.0 mm
Width	50.0 mm
Height	34.0 mm
Product weight	765.00 g
Mounting hole spacing, length	227.0 mm
Cable cross-section, input side	1.0 mm <sup>2</sup>
Cable cross-section, output side	1.0 mm <sup>2</sup>
Wire preparation length, input side	90 mm

## Temperatures &amp; operating conditions

<b>Ambient temperature range</b>	-30...+55 °C
<b>Permitted rel. humidity during operation</b>	5...85 % <sup>1)</sup>
<b>Maximum temperature at tc test point</b>	80 °C
<b>Max.housing temperature in case of fault</b>	110 °C

<sup>1)</sup> Maximum 56 days/year at 85 %

## Lifespan

<b>ECG lifetime</b>	50000 h
---------------------	---------

## Capabilities

<b>Dimmable</b>	Yes
<b>Suitable for fixtures with prot. class</b>	I
<b>Overheating protection</b>	Yes
<b>Overload protection</b>	Yes
<b>Short-circuit protection</b>	Yes
<b>No-load proof</b>	Yes
<b>Dimming interface</b>	1...10 V






## Certificates &amp; standards






<b>Type of protection</b>	IP66/IP67
<b>Standards</b>	Acc. to EN 61347-1/Acc. to EN 61347-2-13/Acc. to EN 55015/Acc. to EN 61547/Acc. to EN 61000-3-2/Acc. to EN 61000-3-3/Acc. to EN 60598-1/Acc. to EN 62384
<b>Approval marks – approval</b>	ENEC / RCM / CCC / EAC

## Logistical data

<b>Temperature range at storage</b>	-40...+85 °C
-------------------------------------	--------------

## DOWNLOAD DATA

File	
	User instruction OPTOTRONIC LED Power Supply
	Addon Technical Information Dimming table for OT (EN)
	Product Datasheet Datasheet OT 100220-24024 DIM P
	Certificates CCC Certificate No. 2018011002043871
	Certificates CB Test Certificate No. SG PSB-LE-00906

	Certificates ENEC Certificate No. U6 18 01 84117 048
	Declarations of conformity EU Declaration of Conformity 3537796
	Declarations of conformity Attestation of Conformity No. N8A 18 01 84117 054
	Declarations of conformity Attestation of Conformity No. E8A 18 01 84117 049
	Declarations of conformity EU Declaration of Conformity OT 24V P_DIMP

## LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4052899545861	Folding carton box 1	306 mm x 73 mm x 46 mm	804.00 g	1.03 dm <sup>3</sup>
4052899545878	Shipping carton box 10	384 mm x 324 mm x 134 mm	8704.00 g	16.67 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

## DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.