



Ledinaire Clear Accent

RS061B G2 LDNR LED5-36/840 PSR II WH

A complete family of recessed spotlight that delivers superior lighting performance. Choose the best fit for every project from fixed/adjustable head and 3 CCTs. Enjoy great reliable performance free of maintenance.

Product data

General information		Operating and electrical	
Light source color	840 neutral white	Input Voltage	220 to 240 V
Light source replaceable	No	Input Frequency	50 or 60 Hz
Number of gear units	1 unit	Inrush current	1 A
Driver/power unit/transformer	Power supply unit regulating	Power Factor (Min)	0.9
Driver included	Yes	Controls and dimming	
Optic type	Beam angle 36°	Dimmable	Yes
Luminaire light beam spread	36°	Mechanical and housing	
Connection	AC power connector C13	Housing Material	Metal-Plastic
Cable	Cable 0.2 m with cable connector	Reflector material	Polycarbonate aluminum coated
Protection class IEC	Safety class II	Optic material	Polycarbonate
Glow-wire test	Temperature 650 °C, duration 30 s	Optical cover/lens material	Polycarbonate
Flammability mark	For mounting on normally flammable surfaces	Fixation material	Steel
CE mark	CE mark	Optical cover/lens finish	Clear
Warranty period	3 years	Overall height	55 mm
Constant light output	No	Overall diameter	80 mm
Number of products on MCB of 16 A type B	100	Color	White
EU RoHS compliant	Yes	Dimensions (Height x Width x Depth)	55 x NaN x NaN mm (2.2 x NaN x NaN in)

Ledinaire Clear Accent

Approval and application

Ingress protection code	IP20 [Finger-protected]
Mech. impact protection code	IK03 [0.3 J]

Initial performance (IEC compliant)

Initial luminous flux (system flux)	500 lm
Luminous flux tolerance	+/-10%
Initial LED luminaire efficacy	91.00 lm/W
Init. Corr. Color Temperature	4000 K
Init. Color Rendering Index	80
Initial chromaticity	(IEC4000K, 0.38, 0.38) <5SDCM
Initial input power	6 W
Power consumption tolerance	+/-10%

Over time performance (IEC compliant)

Median useful life L70B50	35000 h
Lumen maintenance at median useful life* 50000 h	L65

Application conditions


Ambient temperature range	-20 to +40 °C
Maximum dim level	10% (depends on dimmer, ELV)
Suitable for random switching	Not applicable

Product data

Full product code	871951433127300
Order product name	RS061B G2 LDNR LED5-36/840 PSR II WH
EAN/UPC - Product	8719514331273
Order code	929002670132
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	24
Material Nr. (12NC)	929002670132
Copy Net Weight (Piece)	0.110 kg





Dimensional drawing



Cut-out hole diameter - Ø68mm

RS061B G2 LDNR LED5-36/840 PSR II WH

Photometric data



Downlight RS061B G2 LDNR 840 PSR WH-LDD

Downlight RS061B G2 LDNR 840 PSR WH-GUL

Ledinaire Clear Accent

