

# MAGNUM FUTURE LITE 32W I KL. OCHR. Z GNIAZDEM SCHUKO

## WORKPLACE FLOODLIGHTS



LED |  | IK10

### TECHNICAL PARAMETERS

Index:	406225
Ingress protection:	IP54
Impact resistance:	IK10
Nominal power [W]:	32
Colour temperature [K]:	4000
Luminous flux [lm]*:	3600
Supply voltage [V]:	220-240
Electrical protection class:	I
Material of the body:	PP
Colour of the body:	green

\*Tolerance +/- 10%

### CHARACTERISTICS

Compact and light LED floodlight for professional use. It provides uniform and stable directional lighting. Luminaire made of impact-resistant polipropylene (PP). Anti-glare diffuser made od polycarbonate (PC) transmits up to 80% of the light emitted by the diodes. It is equipped with a multi-position arm with a tilt lock of the housing, handles for cable winding and an ergonomic carrying handle.

### APPLICATION

The luminaire will provide precise illumination of the workplace.

# MAGNUM FUTURE LITE 32W I KL. OCHR. Z GNIAZDEM SCHUKO

## WORKPLACE FLOODLIGHTS

### TECHNICAL PARAMETERS TABLE

Light source:	LED module	Dimensions [mm]:	300/400/100
Nominal power [W]:	32	Impact resistance:	IK10
Colour temperature [K]:	4000	Ingress protection:	IP54
Luminous flux [lm]:	3600	Plug type:	UNI-SCHUKO
Supply voltage [V]:	220-240	Socket type:	SCHUKO
Electrical protection class:	I	Sockets:	1
Beam angle [°]:	120	Wire type:	H07RN-F 2×1,0mm
Diffuser material:	PC	Cable length [m]:	3
Diffuser type:	frozen	Net weight of the luminaire [kg]:	2.700
Material of the body:	PP	Index:	406225
Colour of the body:	green	Category type:	workplace floodlights

\*Tolerance+/- 10%

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer.

Revision date: 2020-09-17



Lena Lighting S.A.  
ul. Kórnicka 52  
63-000 Środa Wielkopolska

tel. +48 61 28 60 300  
e-mail: office@lenalighting.pl  
www.lenalighting.pl



The luminaire complies with the EU ROHS Directive 2011/65/UE



This product is a subject to electric and electronic waste equipment regulations (WEEE).



74/2020