

MAGNUM FUTURE LITE 32W II KL. OCHR. UNI-SCHUKO

WORKPLACE FLOODLIGHTS



220-240 V | LED |  | IP54 | IK10

TECHNICAL PARAMETERS

Index:	406249
Ingress protection:	IP54
Impact resistance:	IK10
Nominal power [W]:	32
Colour temperature [K]:	4000
Luminous flux [lm]*:	3600
Supply voltage [V]:	220 - 240
Electrical protection class:	II
Material of the body:	PP
Colour of the body:	green

*Tolerance +/- 10%

CHARACTERISTICS

Compact and light LED floodlight for professional use. It provides uniform and stable directional lighting. Luminaire made of impact-resistant polipropylene (PP). Anti-glare diffuser made od polycarbonate (PC) transmits up to 80% of the light emitted by the diodes. It is equipped with a multi-position arm with a tilt lock of the housing, handles for cable winding and an ergonomic carrying handle.

APPLICATION

The luminaire will provide precise illumination of the workplace.

MAGNUM FUTURE LITE 32W II KL. OCHR. UNI-SCHUKO

WORKPLACE FLOODLIGHTS

TECHNICAL PARAMETERS TABLE

Light source:	LED module	Dimensions [mm]:	300/400/100
Nominal power [W]:	32	Impact resistance:	IK10
Colour temperature [K]:	4000	Ingress protection:	IP54
Luminous flux [lm]:	3600	Plug type:	UNI-SCHUKO
Supply voltage [V]:	220 - 240	Wire type:	H07RN-F 2×1,0mm
Electrical protection class:	II	Cable length [m]:	3
Beam angle [°]:	120	Net weight of the luminaire [kg]:	2.600
Diffuser material:	PC	Index:	406249
Diffuser type:	frozen	Category type:	workplace floodlights
Material of the body:	PP		
Colour of the body:	green		

*Tolerance+/- 10%

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer.

Revision date: 2020-09-17



Lena Lighting S.A.
ul. Kórnicka 52
63-000 Środa Wielkopolska

tel. +48 61 28 60 300
e-mail: office@lenalighting.pl
www.lenalighting.pl



The luminaire complies with the EU ROHS Directive 2011/65/UE



This product is a subject to electric and electronic waste equipment regulations (WEEE).



74/2020