

MAGNUM FUTURE LITE 50W I KL. OCHR. Z GNIAZDEM SCHUKO

WORKPLACE FLOODLIGHTS



LED |  IK10

TECHNICAL PARAMETERS

Index:	406287
Ingress protection:	IP54
Impact resistance:	IK10
Nominal power [W]:	50
Colour temperature [K]:	4000
Luminous flux [lm]*:	5500
Supply voltage [V]:	220-240
Electrical protection class:	I
Material of the body:	PP
Colour of the body:	green

*Tolerance +/- 10%

CHARACTERISTICS

Compact and light LED floodlight for professional use. It provides uniform and stable directional lighting. Luminaire made of impact-resistant polypropylene (PP). Anti-glare diffuser which, despite the matt surface, transmits up to 80% of the light emitted by the diodes. It is equipped with a multi-position arm with a tilt lock of the housing, handles for cable winding and an ergonomic carrying handle.

APPLICATION

The family of durable and handy MAGNUM FUTURE LED XL luminaires has been designed to illuminate larger areas.

MAGNUM FUTURE LITE 50W I KL. OCHR. Z GNIAZDEM SCHUKO

WORKPLACE FLOODLIGHTS

TECHNICAL PARAMETERS TABLE

Light source:	LED module	Dimensions [mm]:	300/480/75
Nominal power [W]:	50	Impact resistance:	IK10
Colour temperature [K]:	4000	Ingress protection:	IP54
Luminous flux [lm]:	5500	Plug type:	UNI-SCHUKO
Supply voltage [V]:	220-240	Socket type:	SCHUKO
Electrical protection class:	I	Sockets:	1
Beam angle [°]:	120	Cable length [m]:	3
Diffuser material:	PC	Net weight of the luminaire [kg]:	3.400
Diffuser type:	frozen	Index:	406287
Material of the body:	PP	Category type:	workplace floodlights
Colour of the body:	green		

*Tolerance+/- 10%

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer.

Revision date: 2020-09-17



Lena Lighting S.A.
ul. Kórnicka 52
63-000 Środa Wielkopolska

tel. +48 61 28 60 300
e-mail: office@lenalighting.pl
www.lenalighting.pl



The luminaire complies with the EU RoHS Directive 2011/65/UE



This product is a subject to electric and electronic waste equipment regulations (WEEE).



74/2020