



# Ledinaire Waterproof Tube Housing

## WT050C 1xTLED L1200

220 to 240 V - 50 or 60 Hz - Safety class II - - - Dust penetration-protected, jet-proof - 5 J vandal-protected - White

The Ledinaire range contains a selection of popular off-the-shelf LED luminaires that comes with the high Philips quality levels at a competitive price. Reliable, energy efficient and affordable – just what you need.

### Product data

General Information	
Protection class IEC	Safety class II
CE mark	CE mark
Material	Polycarbonate
Angle	-
Accessory color	White

Operating and Electrical	
Input Voltage	220 to 240 V
Input Frequency	50 or 60 Hz


  

Mechanical and Housing	
Overall length	1275 mm
Overall width	70 mm
Overall height	84 mm
Dimensions (Height x Width x Depth)	84 x 70 x 1275 mm (3.3 x 2.8 x 50.2 in)

Approval and Application	
Ingress protection code	IP65 [ Dust penetration-protected, jet-proof]
Mech. impact protection code	IK08 [ 5 J vandal-protected]


Product Data	
Full product code	871016336602999
Order product name	WT050C 1xTLED L1200
EAN/UPC - Product	8710163366029
Order code	911401807381
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	12
Material Nr. (12NC)	911401807381
Net Weight (Piece)	0.800 kg



# Ledinaire Waterproof Tube Housing

## Dimensional drawing

WT050C L1200 1 Tube



## Ledinaire Waterproof Tube Housing

