

LEVANTO UGR LED1X3650 G088 T840 MPRZ • 1103384


Product:	Levanto UGR LED1x3650 G088 T840 MPRZ
Order code:	1103384
Family:	Levanto UGR LED
Product group:	Recessed luminaires

GENERAL DATA

Description:	Recessed mounted LED panel Light distribution type: direct Optical system: micro-prismatic diffuser, UGR≤19 Housing: aluminum Colour: white (RAL9016)
Installation:	In modular suspended ceilings (600), in ceilings with cut-out openings (mounting accessories to be ordered separately). Cable, 0.1m, 2x0.75mm2
Environment	Indoor
Application	office, education, corridor, retail, public place

ELECTRICAL DATA

Mains voltage:	220-240V, 50/60Hz	System power*, W:	36
Power factor:	>0,9	Control gear:	ECG on/off
Integrated sensor:	None	Connection:	Cable, 0.1m, 2x0.75mm2

LIGHTING DATA

Light source and cap, W:	LED	Light source included:	yes
Luminaire output*, lm (ta+25°C):	3650	System efficacy, lm/W:	101
CRI (Ra):	80+	CCT, K:	4000
SDCM:	5	Light Distribution:	Symmetrical wide beam (76°...125°)
Distribution Type:	Direct	Beam angle, °:	90
UGR index:	≤19	LED lifetime, h:	50000/L70B50

TECHNICAL DATA

Net weight, kg:	1.8	Quantity in package, pcs:	1
Packaging volume, m3/pcs:	0.0134	Pallet quantity, pcs:	60

STANDARDS

Operating temperature range, °C:	ta 0...+35	Protection class IEC:	II
Ingress protection code:	IP40	Mechanical impact resistance:	IK02
EEC:	A+	Certificates:	CE, RoHS
Warranty:	3 years		

Note: Tolerance range for optical and electrical data: ±10%. Values apply to an ambient temperature of 25°C. NORTHCLIFFE LIGHTING is constantly developing and improving its products. The right is reserved to change any product specifications without prior notification

