


PCE data sheet

article#	2331-1
article description	CEE-connector 63A 3p 1h IP44 POWER TWIST
description long	CEE-connector 63A 3p 1h IP44 POWER TWIST housing material: PA6 rated current: 63A number of poles: 3 (2P+PE) clock-position: 1h rated voltage/frequency: >50V / others contacts: brass, with lamellar spring (CuBe) connection technology: frame terminals with screws IP protection class: IP44
country of origin	AT
customs number	85366990
packaging quantity	2
minimum order quantity	2

ETIM 8.0	EC001320
IEC-ampereage	63 A
Number of poles	3
Voltage acc. EN 60309-2	Other
Clock hour position	1 h
Identification colour	Grey
Degree of protection (IP)	IP44
Connection system	Screwed terminal
Angle of plug	Straight
Cable entry	Swivel
Material	Plastic
Contact material	CuZn
Surface finish contacts	Untreated

a	269 mm
b	107 mm
K (cable Ø)	14,5-36 mm
SW	61 mm
wire flexible	6-16 mm ²
contact screws	200 Ncm
strain relief	1500 Ncm
dismantling length	100 mm
stripping length	15-18 mm



<https://www.pcelectric.at/shop/en/?func=detail&artnr=2331-1>



www.manufacturer-safety.info