


## PCE data sheet

|                     |                                                                                                                                                                                                                                                                         |
|---------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| article#            | <b>21392-4</b>                                                                                                                                                                                                                                                          |
| article description | <b>CEE-connector 20A 2P3W 4h IP67 UL</b>                                                                                                                                                                                                                                |
| description long    | CEE-connector 20A 2P3W 4h IP67 UL (PCE320C4W)<br>housing material: PA6<br>rated current: 16A/20A<br>number of poles: 2P3W (3p)<br>clock position: 4h<br>rated voltage: 120Vac<br>contacts: brass<br>connection technology: screw terminals<br>IP protection class: IP67 |
| GTIN (EAN)          | 9003399187865                                                                                                                                                                                                                                                           |
| country of origin   | AT                                                                                                                                                                                                                                                                      |
| customs number      | 85366990                                                                                                                                                                                                                                                                |
| net weight          | 0.155 kg                                                                                                                                                                                                                                                                |
| packaging quantity  | 10                                                                                                                                                                                                                                                                      |

|                                       |                  |
|---------------------------------------|------------------|
| ETIM 7.0                              | EC001320         |
| IEC-amperage                          | 16 A             |
| Amperage acc. UL/CSA (for UL-version) | 20 A             |
| Number of poles                       | 3                |
| Clock hour position                   | 4 h              |
| Identification colour                 | Yellow           |
| Degree of protection (IP)             | IP67             |
| Connection system                     | Screwed terminal |
| Angle of plug                         | Straight         |
| Cable entry                           | Swivel           |
| Material                              | Plastic          |
| Contact material                      | CuZn             |
| Surface finish contacts               | Untreated        |

|                    |                       |
|--------------------|-----------------------|
| a                  | 132 mm                |
| b                  | 78 mm                 |
| K (cable Ø)        | 9-15 mm               |
| SW                 | 42 mm                 |
| wire flexible      | 1-2,5 mm <sup>2</sup> |
| contact screws     | 100 Ncm               |
| strain relief      | 500 Ncm               |
| dismantling length | 50 mm                 |
| stripping length   | 10-12 mm              |



[www.manufacturer-safety.info](http://www.manufacturer-safety.info)