

PCE data sheet



article#	145-1
article description	CEE-wall mounted socket 125A 5p 1h IP67 POWER TWIST
description long	CEE-wall mounted socket 125A 5p 1h IP67 POWER TWIST housing material: PC/ABS rated current: 125A number of poles: 5 (3P+N+PE) clock-position: 1h rated voltage/frequency: >50V / others contacts: brass, with lamellar spring (CuBe) connection technology: frame terminals with screws cable entry: top, bottom, rear inc. threaded blind cap IP protection class: IP66/IP67
GTIN (EAN)	9003399716904
country of origin	AT
customs number	85366990
net weight	1.852 kg
packaging quantity	1
minimum order quantity	1

ETIM 8.0	EC001321
Model	Surface mounted (plaster)
IEC-amperage	125 A
Number of poles	5
Voltage acc. EN 60309-2	Other
Clock hour position	1 h
Identification colour	Grey
Degree of protection (IP)	IP67
Connection system	Screwed terminal
Cable entry	Swivel
Material	Plastic
Contact material	CuZn
Surface finish contacts	Untreated
Type of fastening	External mounting
Insulated mounting	True
Military model	False

wire flexible	16-50 mm ²
wire solid	16-70 mm ²
contact screws	450 Ncm
dismantling length	100 mm
stripping length	24-27 mm



<https://www.pcelectric.at/shop/en/?func=detail&artnr=145-1>



www.manufacturer-safety.info