


## PCE data sheet

|                        |                                                                                                                                                                                                                                                                                                                                                                     |
|------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| article#               | <b>323-1v</b>                                                                                                                                                                                                                                                                                                                                                       |
| article description    | <b>CEE-flanged socket straight (70x70mm) 32A 3p 1h IP44</b>                                                                                                                                                                                                                                                                                                         |
| description long       | CEE-flanged socket straight (70x70mm) 32A 3p 1h IP44<br>housing material: PA6<br>rated current: 32A<br>number of poles: 3 (2P+PE)<br>clock-position: 1h<br>rated voltage/frequency: >50V / others<br>contacts: brass nickel plated<br>connection technology: screw terminals<br>dimensions (flange/fixing center): 70x70 mm / 56x56 mm<br>IP protection class: IP44 |
| country of origin      | AT                                                                                                                                                                                                                                                                                                                                                                  |
| customs number         | 85366990                                                                                                                                                                                                                                                                                                                                                            |
| packaging quantity     | 10                                                                                                                                                                                                                                                                                                                                                                  |
| minimum order quantity | 10                                                                                                                                                                                                                                                                                                                                                                  |

|                                |                |
|--------------------------------|----------------|
| ETIM 8.0                       | EC001317       |
| IEC-amperage                   | 32 A           |
| Voltage acc. EN 60309-2        | Other          |
| Number of poles                | 3              |
| Clock hour position            | 1 h            |
| Identification colour          | Grey           |
| Degree of protection (IP)      | IP54           |
| Connection system              | Screw terminal |
| Angle of plug                  | Straight       |
| Material                       | Plastic        |
| Contact material               | CuZn           |
| Surface finish contacts        | Nickel-plated  |
| Flange size vertical           | 70 mm          |
| Drill hole distance vertical   | 56 mm          |
| Flange size horizontal         | 70 mm          |
| Drill hole distance horizontal | 56 mm          |

|                    |                        |
|--------------------|------------------------|
| wire flexible      | 2,5-6 mm <sup>2</sup>  |
| wire solid         | 2,5-10 mm <sup>2</sup> |
| contact screws     | 110 Ncm                |
| dismantling length | 50 mm                  |
| stripping length   | 12-14 mm               |



<https://www.pcelectric.at/shop/en/?func=detail&artnr=323-1v>



[www.manufacturer-safety.info](http://www.manufacturer-safety.info)