


PCE data sheet

article#	3252-1
article description	CEE-flanged socket straight (75x75mm) 32A 5p 1h IP67
description long	CEE-flanged socket straight (75x75mm) 32A 5p 1h IP67 housing material: PA6 rated current: 32A number of poles: 5 (3P+N+PE) clock-position: 1h rated voltage/frequency: >50V / others contacts: brass connection technology: screw terminals dimensions (flange/fixing center): 75x75 mm / 60x60 mm IP protection class: IP67
GTIN (EAN)	9003399568305
country of origin	AT
customs number	85366990
net weight	0.260 kg
packaging quantity	10
minimum order quantity	10

ETIM 8.0	EC001317
IEC-ampereage	32 A
Voltage acc. EN 60309-2	Other
Number of poles	5
Clock hour position	1 h
Identification colour	Grey
Degree of protection (IP)	IP67
Connection system	Screwed terminal
Angle of plug	Straight
Material	Plastic
Contact material	CuZn
Surface finish contacts	Untreated
Flange size vertical	75 mm
Drill hole distance vertical	60 mm
Flange size horizontal	75 mm
Drill hole distance horizontal	60 mm

wire flexible	2,5-6 mm ²
wire solid	2,5-10 mm ²
contact screws	110 Ncm
dismantling length	50 mm
stripping length	12-14 mm



<https://www.pcelectric.at/shop/en/?func=detail&artnr=3252-1>



www.manufacturer-safety.info