



PCE data sheet

article#	435-1fd
article description	CEE-flanged socket sloping (106x110) 63A 5p 1h IP67 POWER TWIST
description long	CEE-flanged socket sloping (106x110) 63A 5p 1h IP67 POWER TWIST housing material: PA6 rated current: 63A number of poles: 5 (3P+N+PE) clock-position: 1h rated voltage/frequency: >50V / others contacts: brass, with lamellar spring (CuBe) connection technology: frame terminals with screws dimensions (flange/fixing center): 106x110 mm / 90x90 mm IP protection class: IP66/IP67
GTIN (EAN)	9003399872341
country of origin	AT
customs number	85366990
net weight	0.598 kg
packaging quantity	2
minimum order quantity	2

ETIM 8.0	EC001317
IEC-ampere	63 A
Voltage acc. EN 60309-2	Other
Number of poles	5
Clock hour position	1 h
Identification colour	Grey
Degree of protection (IP)	IP67
Connection system	Screwed terminal
Angle of plug	Angled
Material	Plastic
Contact material	CuZn
Surface finish contacts	Untreated
Flange size vertical	110 mm
Drill hole distance vertical	90 mm
Flange size horizontal	106 mm
Drill hole distance horizontal	90 mm



<https://www.pcelectric.at/shop/en/?func=detail&artnr=435-1fd>



www.manufacturer-safety.info