

# Product data sheet

Specifications



## New Unica - Countdown timer relay 10A 3-wires - white (Z)

NU553518

### Main

Product brand	Schneider Electric
Range	New Unica
Type number	NH3535
Product or component type	Timer

### Complementary

Device presentation	Mechanism with fixing frame
Technology type	Electronic
Number of rocker	1
Actuator	Push-button
[Ue] rated operational voltage	230 V AC 50 Hz
Rated current	10 A
Associated fuse rating	16 A
Colour tint	White (RAL 9003)
Surface finish	Glossy
Number of modules	2 modules
Number of FUNCTION keys	2
Local signalling	Indicator: 1 LED (red)
Number of outputs	1
Control type	Remote control by auxiliary push-button Local control
Time delay	5 min...8 h
Connected auxiliaries	Unlimited number of push-buttons, distance : 50 m
Provided equipment	User manual Fixing frame
Wiring configuration	With neutral
Connections - terminals	Screw terminal
Number of loop terminals	2
Clamping connection capacity	1.5...2.5 mm <sup>2</sup> for solid cable(s) 1.5...2.5 mm <sup>2</sup> for solid stranded cable(s)
Shape of screw head	Pozidriv No 1 and combi

<b>Tightening torque</b>	0.5 N.m
<b>Material</b>	PC (polycarbonate) GF10 FR: casing Metal: terminals Thermoplastic ABS-UV stabilised: central plate Zamak: fixing frame
<b>Device mounting</b>	Flush
<b>Fixing mode</b>	By screws
<b>Type of installation</b>	Indoor installation
<b>Type of packing</b>	Carton
<b>Embedding depth</b>	29 mm
<b>Depth</b>	41 mm
<b>Width</b>	74.5 mm
<b>Height</b>	74.5 mm
<b>Net weight</b>	0.079 kg
<b>Resistance to chemical agents</b>	Resistant to alcohol (70 %) Resistant to alcohol (96 %) Resistant to A-Lactic Acid Resistant to diluted quaternary ammonium Resistant to diluted bleach Resistant to diluted ammonia Resistant to soapy water Resistant to crystal cleaner Resistant to hydrogen peroxide 10 volumes Resistant to hexane

## Environment

<b>Ambient air temperature for operation</b>	5...40 °C
<b>Ambient air temperature for storage</b>	5...40 °C
<b>IP degree of protection</b>	IP20
<b>IK degree of protection</b>	IK04
<b>Environmental characteristic</b>	Window-cleaning fluid Acetone Alcohol Petrol Liquid soap Bleach UV resistant Oil
<b>Standards</b>	EN 301-489-17 EN 60669-2-1 EN 60730-2-7 EN 300-328
<b>Directives</b>	2014/35/EU - low voltage directive 2014/30/EU - electromagnetic compatibility
<b>Product certifications</b>	EAC NF CE NEMKO FIMKO SEMKO VDE

## Packing Units

<b>Unit Type of Package 1</b>	PCE
<b>Number of Units in Package 1</b>	1
<b>Package 1 Weight</b>	110.5 g
<b>Package 1 Height</b>	4.5 cm
<b>Package 1 width</b>	7.5 cm

---

Package 1 Length	7.5 cm
------------------	--------

---

## Offer Sustainability

---

Sustainable offer status	Green Premium product
--------------------------	-----------------------

---

REACH Regulation	<a href="#">REACH Declaration</a>
------------------	-----------------------------------

---

EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
-------------------	--

---

Mercury free	Yes
--------------	-----

---

RoHS exemption information	Yes
----------------------------	-----

---

China RoHS Regulation	<a href="#">China RoHS declaration</a> Product out of China RoHS scope. Substance declaration for your information
-----------------------	---

---

Environmental Disclosure	<a href="#">Product Environmental Profile</a>
--------------------------	---

---

Circularity Profile	<a href="#">End of Life Information</a>
---------------------	---

---

WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
------	---

---