Product data sheet

Specifications



Asfora - hotel card switch - 10AX screwless terminals, cream

EPH6200123

Main

Range	Asfora
Product or component type	Card switch
Device presentation	Complete product
Colour tint	Cream
Type of packing	Flow-pack

Complementary

Device mounting	Flush
Switch function	1-pole 1-way
Local signalling	LED
Power range	2300 W
Rated current	10 A at 250 V AC
Connections - terminals	Screwless terminals
Number of cables	2 cable(s) 2.5 mm²
Cable stiffness	Flexible Rigid Solid stranded
Wire stripping length	13.0 mm
Material	ABS (acrylonitrile butadiene-styrene)
Surface finish	Glossy
Conductor material	Copper
Fixing mode	Screws or claws5170 mm
Height	83 mm
Width	83 mm
Depth	53.0 mm
Projecting depth	23 mm
Net weight	0.0857 kg

Environment

Standards	IEC 60669-1
Product certifications	TSE

	VDE
Quality labels	CE UKR
IP degree of protection	IP20
Ambient air temperature for operation	-540 °C
Packing Units	
Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	85.0 g
Package 1 Height	5.0 cm
Package 1 width	8.0 cm
Package 1 Length	10.0 cm
Unit Type of Package 2	P12
Number of Units in Package 2	1536
Package 2 Weight	167.28 kg
Package 2 Height	131.0 cm
Package 2 width	80.0 cm
Package 2 Length	120.0 cm
Unit Type of Package 3	BB1
Number of Units in Package 3	8
Package 3 Weight	763.0 g
Package 3 Height	9.5 cm
Package 3 width	18.5 cm
Package 3 Length	27.5 cm
Offer Sustainability	
Sustainable offer status	Green Premium product
REACh Regulation	REACh Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information
Environmental Disclosure	Product Environmental Profile
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

18 months

Warranty

Contractual warranty