



### Main

Range of product	Lighting and power sockets
Accessory / separate part category	Lighting accessory
Product or component type	Lamp
Device application	Multi-purpose
Device composition	1 lamp 1 fixing elements 2 cable
Power factor	0,9

### Complementary

Outlet standard	Without socket
Rated lamp wattage	5 W
[Ue] rated operational voltage	120/230 V AC 50/60 Hz
Bulb base	Integral LED
Bulb type	LED
Control type	Built-it switch
Luminous flux	500 lm
Colour temperature	4000 K
Service life in hours	25000 h
Electrical connection	Cable quick connector 3 m supplied Cable quick connector 1 m supplied
Mounting support	Metal parts Cross rails
Fixing mode	Magnetic fixing Screws
Range compatibility	Spacial Thalassa
Length	310 mm
Height	30,5 mm
Colour	Aluminium

### Environment

IP degree of protection	IP20 IEC 60529
Electrical insulation class	Class I
Standards	IEC 60598
Ambient air temperature for operation	-10...60 °C
Ambient air temperature for storage	-16...65 °C

### Lepakojuuma vienības

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	530 g
Package 1 Height	6 cm
Package 1 Width	7,5 cm
Package 1 Length	34 cm

Unit Type of Package 2	CAR
Number of Units in Package 2	20
Package 2 Weight	11,153 kg
Package 2 Height	28 cm
Package 2 Width	35,5 cm
Package 2 Length	42 cm

## Offer Sustainability

REACH regula	<a href="#">REACH Deklarācija</a>
Nesatur REACH SVHC	Jā
ES RoHS direktīva	Atbilstīgs <a href="#">ES RoHS Deklarācija</a>
Nesatur toksiskus smagos metālus	Jā
Nesatur dzīvsudrabu	Jā
Informācija par RoHS izņēmumiem	<a href="#">Jā</a>
Ķīnas RoHS regula	<a href="#">Ķīnas RoHS Deklarācija</a>
WEEE	Eiropas Savienības tirgū no šī produkta ir jāatbrīvojas, ievērojot noteiktu atkritumu savākšanas kārtību, un produkts nedrīkst nonākt sadzīves atkritumu tvertnēs.