

# Product data sheet

## Characteristics

# NSYLA5T5LD2

## Cost-effective LED Lamps - 120/230 V AC - 10W



### Main

Range of product	Lighting and power sockets
Accessory / separate part category	Lighting accessory
Product or component type	Lamp
Device application	Multi-purpose
Device composition	1 lamp 1 fixing elements 2 cable
Power factor	0.9

### Complementary

Outlet standard	Without socket
Rated lamp wattage	10 W
[Ue] rated operational voltage	120/230 V AC 50/60 Hz
Bulb base	Integral LED
Bulb type	LED
Control type	Built-in switch
Luminous flux	1100 lm
Colour temperature	4000 K
Service life in hours	25000 h
Electrical connection	Cable quick connector 3 m supplied Cable quick connector 1 m supplied
Mounting support	Cross rails Metal parts
Fixing mode	Screws Magnetic fixing
Range compatibility	Spacial Thalassa
Length	560 mm
Height	30.5 mm
Colour	Aluminium

### Environment

IP degree of protection	IP20 conforming to IEC 60529
Electrical insulation class	Class I
Standards	IEC 60598
Ambient air temperature for operation	-10...60 °C
Ambient air temperature for storage	-16...65 °C

### Packing Units

Package 1 Weight	0.340 kg
Package 1 Height	49.000 mm
Package 1 width	54.000 mm
Package 1 Length	595.000 mm

## Offer Sustainability

REACH Regulation	<input checked="" type="checkbox"/> REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant <input checked="" type="checkbox"/> EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	<input checked="" type="checkbox"/> Yes
China RoHS Regulation	<input checked="" type="checkbox"/> China RoHS Declaration
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins